



VAT Vakuumventile AG  
CH-9469 Haag, Schweiz

## Product data sheet

**Mini UHV gate valve, Series 010, DN 40 (ID 1½")**  
**Ordering No. 01032-KE12**

### Description

Flange	ISO-KF 40
Actuator	pneumatic, single acting with opening spring
Feedthrough	Bellows

### Technical data

Leak rate	– Valve body	$< 5 \cdot 10^{-10}$ mbar ls <sup>-1</sup>
	– Valve seat	$< 1 \cdot 10^{-9}$ mbar ls <sup>-1</sup>
Pressure range		$1 \cdot 10^{-10}$ mbar to 2 bar (abs)
Differential pressure on the gate		$\leq 2$ bar
Differential pressure at opening		$\leq 30$ mbar
Conductance (molecular flow)		160 ls <sup>-1</sup>
Cycles until first service		50 000
Temperature	– Valve Body	$\leq 250$ °C open / $\leq 200$ °C closed (bake-out max. 24h)
(Maximum values: depending on operating conditions and sealing materials)	– Actuator	$\leq 200$ °C
Heating and cooling rate		$\leq 50$ °C h <sup>-1</sup>
Material	– Valve Body	AISI 304 (1.4301), AISI 316L (1.4435)
	– Gate	AISI 304 (1.4301)
	– Bellows	AISI 316L (1.4404, 1.4435)
Seal	– Bonnet	metal
	– Gate	FKM (Viton®), vulcanized
	– Actuator	FKM (Viton®)
Mounting position		any
Volume of pneumatic actuator		0.06 l / 0.002 ft <sup>3</sup>
Compressed air		5 – 7 bar / 73 – 102 psi
min. – max. overpressure		
Compressed air connection		G ⅛" (⅛" NPT for USA)
Actuation time	– closing	0.7 s
	– opening	0.7 s
Weight		2.2 kg / 4.85 lbs

Created by: SON	Release date: 2012-12-12	1 of 2
Modified by:	Release date:	<b>284358EA</b>



VAT Vakuumventile AG  
CH-9469 Haag, Schweiz

## Product data sheet

**Mini UHV gate valve, Series 010, DN 40 (ID 1½")**

**Ordering No. 01032-KE12**

Behavior in case of compressed air pressure drop

- Valve closed
- Valve open

valve opens  
valve remains open

Behavior in case of power failure

- Valve closed
- Valve open

depending on customer installation  
depending on customer installation

Created by: SON	Release date: 2012-12-12	2 of 2
Modified by:	Release date:	<b>284358EA</b>