



VAT Vakuumventile AG
CH-9469 Haag, Schweiz

Product data sheet

Vacuum gate valve, Series 08.1, DN 63 (ID 2½")
Ordering No. 08136-FA03

Description

Flange	DN 63 Flat flanges with O-ring grooves
Actuator	manual – push rod
Feedthrough	Shaft feedthrough

Technical data

Leak rate	– Valve body – Valve seat	$< 5 \cdot 10^{-9}$ mbar ls ⁻¹ $< 1 \cdot 10^{-9}$ mbar ls ⁻¹
Pressure range		$1 \cdot 10^{-7}$ mbar to 1.6 bar (abs)
Differential pressure on the gate		≤ 1.6 bar
Differential pressure at opening		≤ 30 mbar
Conductance (molecular flow)		1000 ls ⁻¹
Cycles until first service		200 000
Temperature (Maximum values: depending on operating conditions and sealing materials)	– Valve Body – Actuator	≤ 120 °C ≤ 80 °C
Heating and cooling rate		50 °C h ⁻¹
Material	– Valve Body – Mechanism	EN AW-5083 (3.3547), EN AW-6061 (3.3211) AISI 304 (1.4301)
Seal	– Bonnet – Gate – Shaft feedthrough	FKM (Viton®) FKM (Viton®) FKM (Viton®)
Mounting position		any
Weight		2.2 kg / 4.9 lbs

Created by: MAEM	Release date: 2013-06-10	1 of 1
Modified by:	Release date:	260933EA