



VAT Vakuumventile AG
CH-9469 Haag, Schweiz

Product data sheet

Vacuum gate valve, Series 08.2, DN 50 (ID 2'')
Ordering No. 08234-FA06

Description

Flange	DN 50 Flat flanges with O-ring grooves
Actuator	manual – toggle lever
Feedthrough	Shaft feedthrough

Technical data

Leak rate	– Valve body – Valve seat	$< 5 \cdot 10^{-9}$ mbar ls ⁻¹ $< 1 \cdot 10^{-9}$ mbar ls ⁻¹
Pressure range		$1 \cdot 10^{-7}$ mbar to 1.6 bar (abs)
Differential pressure on the gate		≤ 1 bar
Differential pressure at opening		≤ 30 mbar
Conductance (molecular flow)		410 ls ⁻¹
Cycles until first service		50 000
Temperature (Maximum values: depending on operating conditions and sealing materials)	– Valve Body – Actuator	≤ 100 °C ≤ 80 °C
Heating and cooling rate		50 °C h ⁻¹
Material	– Valve Body – Mechanism	EN AW-6082 (3.2315) AISI 301 (1.4310)
Seal	– Bonnet – Gate – Shaft feedthrough	FKM (Viton®) FKM (Viton®) FKM (Viton®)
Mounting position		any
Weight		0.9 kg / 2.0 lbs

Created by: MAEM	Release date: 2013-06-10	1 of 1
Modified by:	Release date:	600778EA