



VAT Vakuumventile AG
CH-9469 Haag, Schweiz

Product data sheet

HV gate valve, Series 091, DN 50 (ID 2'')

Ordering No. 09134-KE14


Description

Flange	ISO-KF 50
Actuator	pneumatic, double acting
Feedthrough	Bellows feedthrough

Technical data

Leak rate	
– Valve body	$< 1 \cdot 10^{-9} \text{ mbar ls}^{-1}$
– Valve seat	$< 1 \cdot 10^{-7} \text{ mbar ls}^{-1}$
Pressure range	$1 \cdot 10^{-8} \text{ mbar}$ to 1.2 bar (abs)
Differential pressure on the gate	$\leq 1.2 \text{ bar}$
Conductance (molecular flow)	250 ls^{-1}

Max. differential pressure at opening in closing and opening direction with influence to the cycle life



– Higher pressure on seat side A, the differential pressure acts in opening direction	$\leq 1.0 \text{ bar}$ with full cycle life
– Higher pressure on counter seat side B, the differential pressure acts in closing direction	$\leq 30 \text{ mbar}$ with full cycle life
– Higher pressure on counter seat side B, the differential pressure acts in closing direction	$\leq 1.0 \text{ bar}$ with reduced cycle life
Cycles until first service	5 000 (unheated and under clean conditions)
Bellows cycles	100 000 (unheated and under clean conditions)
Bake-out temperature	
– Valve body	$\leq 150 \text{ }^\circ\text{C}$ (bake-out max. 24h)
– Actuator	$\leq 100 \text{ }^\circ\text{C}$
Heating and cooling rate	$50 \text{ }^\circ\text{C h}^{-1}$

Created by: LOO	Release date: 2014-07-04	1 of 2
Modified by:	Release date:	603999EA



VAT Vakuumventile AG
CH-9469 Haag, Schweiz

Product data sheet

HV gate valve, Series 091, DN 50 (ID 2'')
Ordering No. 09134-KE14

Material

– Valve body	AISI 304 (1.4301)
– Gate	AISI 304 (1.4301), (1.4308)
– Parts (in contact with media)	A2 Ni-Teflon coated, PEEK
– Bellows	AISI 633, (AM350)

Seal

– Bonnet	FKM (Viton [®])
– Gate	FKM (Viton [®])
– Actuator	FKM (Viton [®])

Mounting position

any

Compressed air

4 – 7 bar / 58 – 102 psi

min. – max. overpressure

Volume of pneumatic actuator

0.08 l / 0.003 ft³

Compressed air connection

M5 (10–32 UNF suitable)

Actuation time

– closing	≤1.5 s
– opening	≤1.5 s

Weight

approx. 3.4 kg / 7.5 lbs

Behavior in case of compressed air pressure drop

– Valve closed	Valve remains closed (≥ 24h)
– Valve open	undefined
– During actuation	undefined

Created by: LOO

Release date: 2014-07-04

2 of 2

Modified by:

Release date:

603999EA