

Product data sheet

HV gate valve Series 091, DN 100 (4") Ordering No. 09140-PE14-0003

Description

ISO-F 100 Flange

Actuator Pneumatic, double acting

Feedthrough **Bellows**

Technical data

Leak rate Valve body $< 1 \cdot 10^{-9} \text{ mbar ls}^{-1}$ < 1 · 10⁻⁷ mbar ls⁻¹ - Valve seat

1 · 10⁻⁸ mbar to 1.2 bar (abs) Pressure range

Differential pressure on the plate ≤ 1.2 bar

Differential pressure at actuation - In opening direction ≤ 1 bar¹

> In closing direction ≤ 30 mbar (1 bar with reduced cycle life)²

Conductance (molecular flow)

Cycles until first service 5 000 (unheated and under clean conditions)

≤ 180 °C Temperature - Valve body ≤ 100 °C (Maximum values: depending - Actuator

on operating conditions and

sealing materials)

Heating and cooling rate 50 °C h-1

Material Valve body AISI 304 (1.4301)

AISI 304 (1.4301, 1.4308) Gate - Bellows AISI 633 (AM350)

- Small parts A2 Ni-PTFE coated, PEEK

Seal Bonnet **FKM** - Gate **FKM**

- Actuator FKM, PU

Mounting position any

Volume of pneumatic actuator 0.25 I / 0.009 ft³

Compressed air 4 - 7 bar / 58 - 102 psi

min. - max. overpressure

Compressed air connection G1/8" (NPT for USA)

≤ 0.5 s Actuation time

Weight 7.3 kg / 16.1 lbs

² Differential pressure supports gate to stay closed. Therefore cycle life reduced due to increased wear of gate seal

Created by: BRR	Release date: 22.10.2021	1/2
Modified by:	Release date:	1131360EA

¹ Differential pressure supports gate to open



Product data sheet

HV gate valve Series 091, DN 100 (4") Ordering No. 09140-PE14-0003

Behavior in case of compressed

air pressure drop

Valve closed
 valve remains closed (≥ 24h)

Valve open undefinedDuring actuation undefined

Behavior in case of power failure

Valve closed depending on customer installation
 Valve open depending on customer installation
 During actuation depending on customer installation

Related documents

Dimensional drawing No. 1095852

Created by: BRR Modified by:	Release date: 22.10.2021 Release date:	2/2 1121260EA
		1131360EA