

Product data sheet

HV gate valve Series 091, DN 200 (8") Ordering No. 09146-PE01

Description

ISO-F 200 Flange

Actuator Manual actuator with detachable handle, self locking

in any position, visual position indicator

Number of turns needed for full stroke Approx. 58 Turns

Feedthrough **Bellows**

Technical data


Leak rate

- Valve body $< 1 \cdot 10^{-9} \text{ mbar Is}^{-1}$ - Valve seat $< 1 \cdot 10^{-7} \, \text{mbar Is}^{-1}$

Pressure range 1 · 10⁻⁸ mbar to 1.2 bar (abs)

Differential pressure on the gate ≤ 1.2 bar Conductance (molecular flow) 9 500 ls⁻¹

Max. differential pressure at opening in closing and opening direction with influence to the cycle life



- Higher pressure on seat side A, the differential pressure

acts in opening direction

≤ 1.0 bar with full cycle life

- Higher pressure on counter seat side B, the differential

pressure acts in closing direction

≤ 30mbar with full cycle life

- Higher pressure on counter seat side B, the differential

pressure acts in closing direction

≤ 1.0 bar with reduced cycle life

Cycles until first service

1 000 (unheated and under clean conditions)

Bellows cycles

10 000 (unheated and under clean conditions)

Bake-out temperature

 Valve body ≤ 150 °C (bake-out max. 24h)

≤ 100 °C - Actuator

50 °C h-1 Heating and cooling rate

Modified by:	Release date:	1003135EA
Created by: BRR	Release date: 24.10.2019	1/2



Product data sheet

HV gate valve Series 091, DN 200 (8") Ordering No. 09146-PE01

Material

- Valve body AISI 304 (1.4301)

Gate
Parts (in contact with media)
AlSI 304 (1.4301), (1.4308)
A2 Ni-Teflon coated, PEEK

- Bellows AISI 633, (AM350)

Seal

 $\begin{array}{ccc} - \ \, \text{Bonnet} & \quad \, & \quad \, \text{FKM (Viton}^{\otimes}) \\ - \ \, \text{Gate} & \quad \, & \quad \, \text{FKM (Viton}^{\otimes}) \end{array}$

Mounting position Any

Weight 28.5 kg / 62.83 lbs

Modified by:	Release date:	1003135EA
Created by: BRR	Release date: 24.10.2019	2/2