

# Description

| Flange   |  | ISO-F 100   |
|--|--|---|
| Actuator   |  | pneumatic, double acting<br>– with solenoid valve<br>– with position indicator                |
| Feedthrough  |  | Bellows   |
| Technical data   |  |   |
| Leak rate  | – Valve body<br>– Valve seat   | < 5 · 10 <sup>-10</sup> mbar ls <sup>-1</sup><br>< 1 · 10 <sup>-9</sup> mbar ls <sup>-1</sup> |
| Pressure range   |  | 1 · 10 <sup>-10</sup> mbar to 1.6 bar (abs)   |
| Differential pressure on the gate  |  | ≤ 1.6 bar   |
| Differential pressure at opening   |  | ≤ 30 mbar   |
| Conductance (molecular flow)   |  | 1740 ls <sup>-1</sup>   |
| Cycles until first service   |  | 50 000 (unheated and under clean conditions)  |
| Temperature<br>(Maximum values: depending<br>on operating conditions and<br>sealing materials) | <ul> <li>Valve Body</li> <li>Actuator</li> <li>Solenoid valve</li> <li>Position indicator</li> </ul> | ≤ 250 °C open / ≤ 200 °C closed (bake-out max. 24h)<br>≤ 200 °C<br>≤ 50 °C<br>≤ 80 °C         |
| Heating and cooling rate   |  | 50 °C h <sup>-1</sup>   |
| Material (main components)   | – Valve Body<br>– Mechanism<br>– Bellows   | AISI 304 (1.4301)<br>AISI 316L (1.4404), AISI 304 (1.4301)<br>AISI 316L (1.4404, 1.4435)      |
| Seal   | – Bonnet<br>– Gate<br>– Actuator   | metal<br>FKM (Viton <sup>®</sup> ), vulcanized<br>FKM (Viton <sup>®</sup> ), NBR              |
| Mounting position  |  | any   |
| Volume of pneumatic actuator   |  | 0.11 I / 0.0038 ft <sup>3</sup>   |
| Compressed air<br>min. – max. overpressure   |  | 4 – 7 bar / 58 – 102 psi  |
| Compressed air connection  |  | G¼" (½" NPT for USA)  |

| Created by: JOM | Release date: 16.05.2014 | 1/2      |
|-----------------|--------------------------|----------|
| Modified by:    | Release date:            | 750438EA |




## Product data sheet UHV gate valve, Series 108, DN 100 (ID 4'') Ordering No. 10840-PE44

| Actuation time                                   | – closing<br>– opening                               | 1.2 s<br>1.2 s                    |
|--|--|-----------------------------------|
| Weight   |  | 12.6 kg / 27.8 lbs                |
| Behavior in case of compressed air pressure drop | <ul> <li>Valve closed</li> <li>Valve open</li> </ul> | valve remains closed<br>undefined |
| Behavior in case of power failure                | <ul><li>Valve closed</li><li>Valve open</li></ul>    | valve remains closed valve closes |

### **Electrical connections**

#### Solenoid valve


| Туре    | 4/2 way          |
|---------|------------------|
| Voltage | Defined by order |



#### Wiring diagram

#### **Position indicator**

| Туре         | Micro switch        |
|--------------|---------------------|
| Voltage      | $\leq 50$ V AC / DC |
| Current max. | ≤ 1.2 A             |



Wiring diagram

| Created by: JOM | Release date: 16.05.2014 | 2/2      |
|-----------------|--------------------------|----------|
| Modified by:    | Release date:            | 750438EA |