

Product data sheet UHV gate valve, Series 108, DN 200 (ID 8'') Ordering No. 10846-PE44-0007

Description

2000.10.00		
Flange		ISO-F 200
Actuator		pneumatic, double acting – with solenoid valve – with position indicator
Feedthrough		Bellows
Technical data		
Leak rate	– Valve body – Valve seat	< 5 · 10 ⁻¹⁰ mbar ls ⁻¹ < 1 · 10 ⁻⁹ mbar ls ⁻¹
Pressure range		$1 \cdot 10^{-10}$ mbar to 1.6 bar (abs)
Differential pressure on the gate		≤ 1.6 bar
Differential pressure at opening		≤ 30 mbar
Conductance (molecular flow)		12 200 ls ⁻¹
Cycles until first service		50 000 (unheated and under clean conditions)
Temperature (Maximum values: depending on operating conditions and sealing materials)	 Valve Body Actuator Solenoid valve Position indicator 	≤ 250 °C open / ≤ 200 °C closed (bake-out max. 24h) ≤ 200 °C ≤ 50 °C ≤ 80 °C
Heating and cooling rate		50 °C h ⁻¹
Material (main components)	– Valve Body – Mechanism – Bellows	AISI 304 (1.4301) AISI 316L (1.4404), AISI 304 (1.4301) AISI 316L (1.4404, 1.4435)
Seal	– Bonnet – Gate – Actuator	metal FKM (Viton [®]), vulcanized FKM (Viton [®]), NBR
Mounting position		any
Volume of pneumatic actuator		0.25 I / 0.0087 ft ³
Compressed air min. – max. overpressure		4 – 7 bar / 58 – 102 psi
Compressed air connection		G1⁄8" (1⁄8" NPT for USA)
Actuation time	– closing – opening	2 s 2 s
Weight		34 kg / 75 lbs
Behavior in case of compressed air pressure drop	 Valve closed Valve open 	valve remains closed undefined
Behavior in case of power failure	Valve closedValve open	valve remains closed valve closes

Created by: BRR	Release date: 07.07.2017	1/2
Modified by:	Release date:	901951EA




Product data sheet UHV gate valve, Series 108, DN 200 (ID 8'') Ordering No. 10846-PE44-0007

Electrical connections

Solenoid valve


Type Voltage 4/2 way Defined by order



Wiring diagram

Position indicator

Туре	Micro switch
Voltage	\leq 50 V AC / DC
Current max.	≤ 1.2 A



Wiring diagram

Created by: BRR	Release date: 07.07.2017	2/2
Modified by:	Release date:	901951EA