

### Product data sheet

# UHV gate valve, Series 108, DN 250 (ID 10") Ordering No. 10848-TE24

## **Description**

Flange ASA-LP 250

Actuator pneumatic, double acting

with position indicator

Feedthrough Bellows

**Technical data** 

Leak rate - Valve body  $< 5 \cdot 10^{-10}$  mbar ls<sup>-1</sup>

- Valve seat  $< 1 \cdot 10^{-9}$  mbar Is<sup>-1</sup>

Pressure range  $1 \cdot 10^{-10}$  mbar to 1.2 bar (abs)

Differential pressure on the gate  $\leq$  1.2 bar

Differential pressure at opening  $\leq$  30 mbar

Conductance (molecular flow) 19 990 ls<sup>-1</sup>

Cycles until first service 50 000 (unheated and under clean conditions)

Temperature – Valve Body ≤ 250 °C open / ≤ 200 °C closed (bake-out max. 24h)

(Maximum values: depending — Actuator ≤ 200 °C on operating conditions and — Position indicator ≤ 80 °C

sealing materials)

Heating and cooling rate 50 °C h<sup>-1</sup>

Material (main components) – Valve Body AISI 304 (1.4301)

- Mechanism AISI 316L (1.4404), AISI 304 (1.4301)

- Bellows AISI 316L (1.4404, 1.4435)

Seal – Bonnet metal

Gate
 Actuator
 FKM (Viton®), O-ring
 FKM (Viton®), NBR

Mounting position any

Volume of pneumatic actuator 0.35 I / 0.0122 ft<sup>3</sup>

Compressed air 5-7 bar / 73-102 psi

min. - max. overpressure

Compressed air connection 1/8" ISO / NPT

| Created by: SON | Release date: 2015-02-24 | 1 of 2   |
|-----------------|--------------------------|----------|
| Modified by:    | Release date:            | 299149EA |



## **Product data sheet**

# UHV gate valve, Series 108, DN 250 (ID 10") Ordering No. 10848-TE24

Actuation time - closing 4 s - opening 4 s

50 kg / 110 lbs

Weight Behavior in case of compressed valve remains closed - Valve closed

air pressure drop undefined - Valve open


depending on customer installation Behavior in case of power failure - Valve closed

- Valve open depending on customer installation

#### **Position indicator**

Type Micro switch Voltage ≤ 50 V AC / DC

Current max. ≤ 1.2 A



Wiring diagram

| Created by: SON | Release date: 2015-02-24 | 2 of 2   |
|-----------------|--------------------------|----------|
| Modified by:    | Release date:            | 299149EA |