

Product data sheet UHV gate valve, Series 108, DN 320 (ID 12'') Ordering No. 10850-PE24

Description

Flange		ISO-F 320
Actuator		pneumatic, double acting – with position indicator
Feedthrough		Bellows
Technical data		
Leak rate	– Valve body – Valve seat	< 5 · 10 ⁻¹⁰ mbar ls ⁻¹ < 1 · 10 ⁻⁹ mbar ls ⁻¹
Pressure range		$1 \cdot 10^{-10}$ mbar to 1.2 bar (abs)
Differential pressure on the gate		≤ 1.2 bar
Differential pressure at opening		≤ 30 mbar
Conductance (molecular flow)		29 130 ls ⁻¹
Cycles until first service		50 000 (unheated and under clean conditions)
Temperature (Maximum values: depending on operating conditions and sealing materials)	 Valve Body Actuator Position indicator 	≤ 250 °C open / ≤ 200 °C closed (bake-out max. 24h) ≤ 200 °C ≤ 80 °C
Heating and cooling rate		50 °C h ⁻¹
Material (main components)	– Valve Body – Mechanism – Bellows	AISI 304 (1.4301) AISI 316L (1.4404), AISI 304 (1.4301) AISI 316L (1.4404, 1.4435)
Seal	– Bonnet – Gate – Actuator	metal FKM (Viton [®]), O-ring FKM (Viton [®]), NBR
Mounting position		any
Volume of pneumatic actuator		0.48 I / 0.0167 ft ³
Compressed air min. – max. overpressure		5 – 7 bar / 73 – 102 psi
Compressed air connection		1⁄6" ISO / NPT

Created by: SON	Release date: 2013-01-15	1 of 2
Modified by:	Release date:	299156EA




Product data sheet UHV gate valve, Series 108, DN 320 (ID 12'') Ordering No. 10850-PE24

Actuation time	– closing – opening	5 s 5 s
Weight		95 kg / 210 lbs
Behavior in case of compressed air pressure drop	– Valve closed – Valve open	valve remains closed undefined
Behavior in case of power failure	– Valve closed – Valve open	depending on customer installation depending on customer installation

Position indicator

Туре	Micro switch
Voltage	\leq 50 V AC / DC
Current max.	≤ 1.2 A



Wiring diagram

Created by: SON	Release date: 2013-01-15	2 of 2
Modified by:	Release date:	299156EA