



VAT Vakuumventile AG
CH-9469 Haag, Schweiz

Product data sheet

HV gate valve Series 111, DN 160 (ID 6")

Ordering No. 11144-CE08

Description

Flange	CF-F 160
Actuator	Manual, handwheel – with position indicator
Feedthrough	Bellows

Technical data

Leak rate	– Valve body	$< 1 \cdot 10^{-9}$ mbar ls ⁻¹
	– Valve seat	$< 1 \cdot 10^{-9}$ mbar ls ⁻¹
Pressure range		$1 \cdot 10^{-8}$ mbar to 1.6 bar (abs)
Differential pressure on the gate		≤ 1.6 bar
Differential pressure at opening		≤ 30 mbar
Conductance (molecular flow)		1740 ls ⁻¹
Cycles until first service		200 000 (unheated and under clean conditions)
Temperature	– Valve Body	≤ 150 °C (bake-out max. 24h)
(Maximum values: depending on operating conditions and sealing materials)	– Actuator	≤ 120 °C
	– Position indicator	≤ 80 °C
Heating and cooling rate		50 °C h ⁻¹
Material (main components)	– Valve Body	AISI 304 (1.4301)
	– Mechanism	AISI 316L (1.4404), AISI 304 (1.4301)
	– Bellows	AISI 316L (1.4404, 1.4435)
	– Bushing	Hydrocarbonate
Seal	– Bonnet	FKM (Viton®)
	– Gate	FKM (Viton®), vulcanized
Mounting position		any
Weight		16 kg / 35.3 lbs

Created by: GIMI	Release date: 04.05.2022	1/2
Modified by:	Release date:	1161236EA

