

Product data sheet

HV gate valve, Series 111, DN 200 (8") Ordering No. 11146-TE44

Description

ASA-LP 200 Flange

Actuator pneumatic, double acting

> with solenoid valve with position indicator

Feedthrough **Bellows**

Technical data

 Valve body $< 1 \cdot 10^{-9} \text{ mbar Is}^{-1}$ Leak rate

 $< 1 \cdot 10^{-9} \text{ mbar ls}^{-1}$ Valve seat

1 · 10⁻⁸ mbar to 1.6 bar (abs) Pressure range

Differential pressure on the gate ≤ 1.6 bar Differential pressure at opening ≤ 30 mbar Conductance (molecular flow) 12 200 Is-1

Cycles until first service 200 000 (unheated and under clean conditions)

≤ 150 °C (bake-out max. 24h) Temperature Valve Body

≤ 120 °C (Maximum values: depending Actuator - Solenoid valve ≤ 50 °C on operating conditions and ≤ 80 °C sealing materials) - Position indicator

Heating and cooling rate 50 °C h-1

Material (main components) - Valve Body **AISI 304** (1.4301)- Mechanism AISI 316L (1.4404)

> - Bellows AISI 316L (1.4404, 1.4435)

 Bushing Hydrocarbonate

Seal Bonnet FKM (Viton®)

> Gate FKM (Viton®), vulcanized Actuator FKM (Viton®), NBR

Mounting position any

Volume of pneumatic actuator 0.25 I / 0.0087 ft3

Compressed air 4 - 7 bar / 58 - 102 psi

min. - max. overpressure

G1/4" (1/4" NPT for USA) Compressed air connection

Actuation time - closing 2 s opening 2 s

Weight 34 kg / 75 lbs

 Valve closed valve remains closed Behavior in case of compressed

air pressure drop Valve open undefined

Behavior in case of power failure - Valve closed valve remains closed

Valve open valve closes

Created by: SAVI	Release date: 20.07.2021	1/2
Modified by:	Release date:	1117245EA



Product data sheet


HV gate valve, Series 111, DN 200 (8") Ordering No. 11146-TE44

Electrical connections

Solenoid valve

Type 4/2 way

Voltage Defined by order



Wiring diagram

Position indicator

Type Micro switch Voltage $\leq 50 \text{ V AC / DC}$ Current max. $\leq 1.2 \text{ A}$

OPEN

CLOSED

Valve/Ventil/Vanne
OPEN CLOSED

1,2 connected Front view 6,5 - connected

Wiring diagram

Modified by:	Release date:	1117245EA
Created by: SAVI	Release date: 20.07.2021	2/2