



VAT Vakuumventile AG
CH-9469 Haag, Schweiz

Product data sheet

Vacuum gate valve, Series 121, DN 80 (ID 3'')
Ordering No. 12138-PA03

Description

| | |
|-------------|-------------------|
| Flange | ISO-F 80 |
| Actuator | manual |
| Feedthrough | Shaft feedthrough |

Technical data

| | | |
|---|---------------------|---|
| Leak rate | – Valve body | $< 1 \cdot 10^{-9}$ mbar ls ⁻¹ |
| | – Valve seat | $< 1 \cdot 10^{-9}$ mbar ls ⁻¹ |
| Pressure range | | $1 \cdot 10^{-7}$ mbar to 1.6 bar (abs) |
| Differential pressure on the gate | | ≤ 1.6 bar |
| Differential pressure at opening | | ≤ 30 mbar |
| Conductance (molecular flow) | | 1 000 ls ⁻¹ |
| Cycles until first service | | 5 000 (unheated and under clean conditions) |
| Temperature | – Valve body | ≤ 120 °C |
| (Maximum values: depending on operating conditions and sealing materials) | – Actuator | ≤ 80 °C |
| Heating and cooling rate | | 30 °C h ⁻¹ |
| Material | – Valve body | EN AW-5083 (3.3547) |
| | – Gate | AISI 304 (1.4301) |
| | – Mechanism | AISI 301 (1.4310), AISI 304 (1.4301), AISI 420 (1.4034) |
| | – Shaft feedthrough | AISI 303 (1.4305) |
| Seal | – Bonnet | FKM (Viton®) |
| | – Gate | FKM (Viton®), O-ring |
| Mounting position | | any |
| Weight | | 3.8 kg / 8.4 lbs |

| | | |
|-----------------|--------------------------|-----------------|
| Created by: SON | Release date: 2013-02-01 | 1 of 1 |
| Modified by: | Release date: | 256428EA |