



VAT Vakuumventile AG
CH-9469 Haag, Schweiz

Product data sheet

Vacuum gate valve, Series 121, DN 160 (ID 6'')
Ordering No. 12144-JA24

Description

Flange	JIS 160
Actuator	Pneumatic, double acting – with position indicator
Feedthrough	Shaft feedthrough

Technical data

Leak rate	– Valve body	$< 1 \cdot 10^{-9}$ mbar ls ⁻¹
	– Valve seat	$< 1 \cdot 10^{-9}$ mbar ls ⁻¹
Pressure range		$1 \cdot 10^{-7}$ mbar to 1.6 bar (abs)
Differential pressure on the gate		≤ 1.6 bar
Differential pressure at opening		≤ 30 mbar
Conductance (molecular flow)		6 000 ls ⁻¹
Cycles until first service		100 000 (unheated and under clean conditions)
Temperature	– Valve body	≤ 120 °C
(Maximum values: depending on operating conditions and sealing materials)	– Actuator	≤ 80 °C
	– Position indicator	≤ 80 °C
Heating and cooling rate		30 °C h ⁻¹
Material	– Valve body	EN AC-42100 (3.2371)
	– Mechanism	EN AW-6082 (3.2315)
Seal	– Bonnet	FKM (Viton®)
	– Gate	FKM (Viton®), O-ring
	– Actuator	FKM (Viton®), NBR (BUNA N®)
Mounting position		any
Volume of pneumatic actuator		0.5 l / 0.018 ft ³
Compressed air		4–7 bar / 58–102 psi
min. – max. overpressure		
Compressed air connection		M5 (10–32 UNF suitable)
Actuation time	– closing	2.0 s
	– opening	2.0 s
Weight		9.0 kg / 20 lbs

Created by: SON	Release date: 2016-06-09	1 of 2
Modified by:	Release date:	222329EA



VAT Vakuumventile AG
CH-9469 Haag, Schweiz


Product data sheet

Vacuum gate valve, Series 121, DN 160 (ID 6'')
Ordering No. 12144-JA24

- | | | |
|--|----------------|--------------------------------------|
| Behavior in case of compressed air pressure drop | - Valve closed | - valve remains closed |
| | - Valve open | - undefined |
| Behavior in case of power failure | - Valve closed | - depending on customer installation |
| | - Valve open | - depending on customer installation |

Position indicator

Type	Micro Switch
Voltage	≤ 250 V AC ≤ 50 V DC
Current max.	≤ 2.0 A ≤ 1.2 A



Wiring diagram