



VAT Vakuumventile AG
CH-9469 Haag, Schweiz

Product data sheet

HV gate valve, Series 140, DN 100 (ID 4'')
Ordering No. 14040-PE01

Description

Flange	ISO-F 100
Actuator	Manual, handwheel
Feedthrough	Rotary feedthrough

Technical data

Leak rate	– Valve body	$< 1 \cdot 10^{-9} \text{ mbar ls}^{-1}$
	– Valve seat	$< 1 \cdot 10^{-9} \text{ mbar ls}^{-1}$
Pressure range		$1 \cdot 10^{-8} \text{ mbar to 2 bar (abs)}$
Differential pressure on the gate		$\leq 2 \text{ bar}$
Differential pressure at opening		$\leq 30 \text{ mbar}$
Conductance (molecular flow)		$1\,740 \text{ ls}^{-1}$
Cycles until first service	– Unheated and under clean conditions	200 000
Temperature (Maximum values: depending on operating conditions and sealing materials)	– Valve body	$\leq 150 \text{ }^{\circ}\text{C}$
	– Actuator	$\leq 80 \text{ }^{\circ}\text{C}$
Heating and cooling rate		$50 \text{ }^{\circ}\text{C h}^{-1}$
Material (main components)	– Valve body	AISI 304 (1.4301)
	– Mechanism	AISI 304 (1.4301)
Seal	– Bonnet	FKM (Viton [®]), Vulcanized
	– Gate	FKM (Viton [®]), O-ring
	– Actuator	FKM (Viton [®]), NBR
Mounting position		any
Weight		15 kg / 33lbs

Created by: JOM	Release date: 2015-02-19	1 of 1
Modified by:	Release date:	787830EA