



VAT Vakuumventile AG
CH-9469 Haag, Schweiz

Product data sheet

HV gate valve, Series 140, DN 100 (ID 4")
Ordering No. 14040-UE01-0006

Description

Flange	CF-F 100 UNF
Actuator	Manual, handwheel
Feedthrough	Rotary feedthrough

Technical data

Leak rate	– Valve body	$< 1 \cdot 10^{-9}$ mbar ls ⁻¹
	– Valve seat	$< 1 \cdot 10^{-9}$ mbar ls ⁻¹
Pressure range		$1 \cdot 10^{-8}$ mbar to 2 bar (abs)
Differential pressure on the gate		≤ 2 bar
Differential pressure at opening		≤ 30 mbar
Conductance (molecular flow)		1 700 ls ⁻¹
Cycles until first service		200 000 Unheated and under clean conditions
Temperature	– Valve body	≤ 150 °C
(Maximum values: depending on operating conditions and sealing materials)	– Manual actuator	≤ 80 °C
Heating and cooling rate		50 °C h ⁻¹
Material (main components)	– Valve body	AISI 304 (1.4301)
	– Mechanism	AISI 301 (1.4310), AISI 304 (1.4301), AISI 420 (1.4034), AISI 420D (1.4037), AISI 430 (1.4016)
Seal	– Bonnet	FKM (Viton®), O-ring
	– Gate	FKM (Viton®), O-ring
	– Actuator	FKM (Viton®), NBR
Mounting position		Any
Weight		13 kg / 28 lbs

Created by: DUE	Release date: 04.02.2016	1/1
Modified by:	Release date:	829788EA