



VAT Vakuumventile AG  
CH-9469 Haag, Schweiz

## Product data sheet

**HV gate valve, Series 140, DN 160 (6")**  
**Ordering No. 14044-TE28**

### Description

Flange	ASA-LP 160
Actuator	Pneumatic, with 3-position actuator – with position indicator
Feedthrough	Rotary feedthrough

### Technical data

Leak rate	– Valve body	$< 1 \cdot 10^{-9}$ mbar ls <sup>-1</sup>
	– Valve seat	$< 1 \cdot 10^{-9}$ mbar ls <sup>-1</sup>
Pressure range		$1 \cdot 10^{-8}$ mbar to 2 bar (abs)
Differential pressure on the gate		$\leq 2$ bar
Differential pressure at opening		$\leq 30$ mbar
Conductance (molecular flow)	– Nominal	5'150 ls <sup>-1</sup>
	– Min. adjustable	7.5 ls <sup>-1</sup>
Cycles until first service	– Unheated and under clean conditions	200'000
Temperature (Maximum values: depending on operating conditions and sealing materials)	– Valve body	$\leq 150$ °C
	– Actuator	$\leq 50$ °C
	– Position indicator	$\leq 80$ °C
Heating and cooling rate		50 °C h <sup>-1</sup>
Material (main components)	– Valve body	AISI 304 (1.4301)
	– Mechanism	AISI 304 (1.4301), AISI 301 (1.4310), AISI 316L (1.4404)
Seal	– Bonnet	FKM (Viton®), vulcanized
	– Gate	FKM (Viton®), O-ring
	– Actuator	FKM (Viton®), NBR
Mounting position		any
Volume of pneumatic actuator		0.96 l / 0.034 ft <sup>3</sup>
Compressed air min. – max. overpressure		4 – 7 bar / 58 – 102 psi
Compressed air connection		G $\frac{1}{8}$ " ( $\frac{1}{8}$ " NPT for USA)
Actuation time	– closing	$\leq 3.5$ s
	– opening	$\leq 3.5$ s
Weight		30 kg / 66 lbs

Created by: NIW	Release date: 27.10.2020	1/2
Modified by:	Release date:	<b>1061114EA</b>



VAT Vakuumventile AG  
CH-9469 Haag, Schweiz

## Product data sheet


**HV gate valve, Series 140, DN 160 (6")**  
**Ordering No. 14044-TE28**

Behavior in case of compressed air pressure drop	– Valve closed – Valve open – Middle position	valve remains closed undefined undefined
Behavior in case of power failure	– Valve closed – Valve open – Middle position	depending on customer installation depending on customer installation depending on customer installation
Valve position indication		visual (mechanical)

## Electrical connections

### Position indicator

Type	Micro switch	
Voltage	≤ 250 V AC	≤ 50 V DC
Current max.	≤ 5 A	≤ 3 A



Wiring diagram

Created by: NIW	Release date: 27.10.2020	2/2
Modified by:	Release date:	<b>1061114EA</b>