



VAT Vakuumventile AG  
CH-9469 Haag, Schweiz

## Product data sheet

**HV gate valve, Series 140, DN 200 (8")**  
**Ordering No. 14046-PE06**

### Description

Flange	ISO-F 200
Actuator	Manual, hand lever
Feedthrough	Rotary feedthrough

### Technical data

Leak rate	– Valve body	$< 1 \cdot 10^{-9}$ mbar ls <sup>-1</sup>
	– Valve seat	$< 1 \cdot 10^{-9}$ mbar ls <sup>-1</sup>
Pressure range		$1 \cdot 10^{-8}$ mbar to 2 bar (abs)
Differential pressure on the gate		$\leq 2$ bar
Differential pressure at opening		$\leq 30$ mbar
Conductance (molecular flow)		12 200 ls <sup>-1</sup>
Cycles until first service	– Unheated and under clean conditions	200 000 (valve in horizontal position)
Temperature	– Valve body	$\leq 150$ °C
(Maximum values: depending on operating conditions and sealing materials)	– Actuator	$\leq 80$ °C
	–	
Heating and cooling rate		50 °C h <sup>-1</sup>
Material (main components)	– Valve body	AISI 304 (1.4301)
	– Mechanism	AISI 304 (1.4301)
Seal	– Bonnet	FKM (Viton®), Vulcanized
	– Gate	FKM (Viton®), O-ring
	– Actuator	FKM (Viton®), NBR
Mounting position		any
Weight		30 kg / 66 lbs

Created by: BISS	Release date: 19.02.2018	1/1
Modified by:	Release date:	<b>928104EA</b>