

Product data sheet

HV gate valve, Series 140, DN 200 (8") Ordering No. 14046-UE28

Description

Flange CF-F 200 UNF

Actuator Pneumatic, with 3-position actuator

with position indicator

Feedthrough Rotary feedthrough

Technical data

Leak rate - Valve body $< 1 \cdot 10^{-9}$ mbar Is⁻¹

– Valve seat < 1 · 10⁻⁰ mbar ls⁻¹</p>

Pressure range $1 \cdot 10^{-8}$ mbar to 2 bar (abs)

Differential pressure on the gate $\leq 2 \text{ bar}$

Differential pressure at opening \leq 30 mbar

Conductance (molecular flow) – Nominal 12'200 ls⁻¹

Min. adjustable
 10 ls⁻¹

Cycles until first service – Unheated and under

clean conditions

Temperature – Valve body ≤ 150 °C

(Maximum values: depending — Actuator ≤ 50 °C on operating conditions and — Position indicator ≤ 80 °C

sealing materials)

Heating and cooling rate 50 °C h⁻¹

Material (main components) – Valve body AISI 304 (1.4301)

- Mechanism AISI 304 (1.4301), AISI 301 (1.4310)

200'000

Seal – Bonnet FKM (Viton®), vulcanized

- Gate
 - Actuator
 FKM (Viton®), O-ring
 FKM (Viton®), NBR

Mounting position any

Volume of pneumatic actuator 0.96 I / 0,034 ft³

Compressed air 4-7 bar / 58-102 psi

min. - max. overpressure

Compressed air connection G1/8" (1/8" NPT for USA)

Actuation time - closing $\leq 3.5 \text{ s}$

- opening ≤ 3.5 s

Weight 36 kg / 79 lbs

Created by: NIW Modified by:	Release date: 24.10.2020 Release date:	1/2 1060942EA
		1060842EA



Product data sheet

HV gate valve, Series 140, DN 200 (8") Ordering No. 14046-UE28

Behavior in case of compressed

air pressure drop

- Valve closed

valve remains closed

Valve openMiddle position

undefined undefined

Behavior in case of power failure

Valve closedValve open

- Middle position

depending on customer installation depending on customer installation

depending on customer installation

Valve position indication

visual (mechanical)

Electrical connections

Position indicator

Type Micro switch

Voltage \leq 250 V AC \leq 50 V DC

Current max. $\leq 5 \text{ A} \leq 3 \text{ A}$

2	151.	OPEN			
3 INTERMEDIATE					
<u>6</u>		CLOSED			
	Valve/Ventil/Vanne				
		OPEN	INTERMEDIATE	CLOSED	
	1,2	connected	~	=	
	4,3		connected	-	
Front view	6,5		-	connected	

Wiring diagram

Created by: NIW	Release date: 24.10.2020	2/2
Modified by:	Release date:	1060842EA