

Product data sheet Low particle gate valve, Series 150, DN 160 (ID 6") Ordering No. 15044-PA24

Description

ISO-F 160 Flange

Actuator Pneumatic, double acting

with position indicator

Feedthrough Shaft feedthrough

Technical data

< 1 · 10⁻⁹ mbar ls⁻¹ Valve body Leak rate

 $< 1 \cdot 10^{-9} \, \text{mbar ls}^{-1}$ Valve seat

 $1 \cdot 10^{-7}$ mbar to 1 bar (abs) Pressure range

Differential pressure on the gate ≤ 1.2 bar

Differential pressure at opening ≤ 30 mbar 6 000 ls⁻¹ Conductance (molecular flow)

Cycles until first service 500 000 (unheated and under clean conditions)

≤ 120 °C (bake-out max. 24h) **Temperature** Valve Body

- Actuator (Maximum values: depending ≤ 100 °C on operating conditions and - Position indicator ≤ 80 °C

sealing materials)

Heating and cooling rate 30 °C h⁻¹

- Valve Body Material (main components) EN AW-6082 (3.2315)

- Gate EN AW-6082 (3.2315) - Shaft **AISI 303** (1.4305)

Seal Bonnet

FKM (Viton®) FKM (Viton®), vulcanized - Gate

- Actuator FKM (Viton®)

Mounting position Any

0.46 I / 0.016 ft³ Volume of pneumatic actuator

4 - 7 bar / 58 - 102 psi Compressed air

min. - max. overpressure

Compressed air connection M5 (10-32 UNF suitable)

Created by: MAY	Release date: 15.07.2014	1/2
Modified by:	Release date:	760752EA



Product data sheet Low particle gate valve, Series 150, DN 160 (ID 6") Ordering No. 15044-PA24

Actuation time - closing $\leq 3.1 \text{ s}$ - opening $\leq 3.1 \text{ s}$

Weight 11.8 kg / 26.0 lbs

Behavior in case of compressed — Valve closed — Undefined (not mechanically locked)

air pressure drop – Valve open - Undefined (not mechanically locked)

Behavior in case of power failure — Valve closed — Depending on customer installation — Valve open — Depending on customer installation


Electrical connections

Position indicator

Type Micro switch

Voltage ≤ 250 V AC ≤ 50 V DC

Current max. \leq 2 A \leq 1.2 A



Wiring diagram

Created by: MAY	Release date: 15.07.2014	2/2
Modified by:	Release date:	760752EA