

Product data sheet

Pendulum valve, Series 162, DN 200 (ID 8") Ordering No. 16246-TA21

Description

ASA-LP 200 Flange

Actuator - pneumatic, single acting, with closing spring (NC)

with position indicator

Feedthrough Rotary feedthrough

Technical data

 $< 1 \cdot 10^{-9} \, \text{mbar ls}^{-1}$ Valve body Leak rate

 $< 1 \cdot 10^{-9} \text{ mbar ls}^{-1}$ - Valve seat

 $1 \cdot 10^{-8}$ mbar to 1.2 bar (abs) Pressure range

Differential pressure on the gate ≤ 1.2 bar Differential pressure at opening ≤ 10 mbar 11 000 ls⁻¹ Conductance (molecular flow)

200 000 (unheated and under clean conditions) Cycles until first service

≤ 120 °C Temperature Valve body ≤ 80 °C (Maximum values: depending Actuator on operating conditions and Position indicator ≤ 80 °C

sealing materials)

 \leq 30 °C h⁻¹ Heating and cooling rate

Material Valve body, gate,

> sealing ring EN AW-5083 (3.3547), EN AW-6082 (3.2315)

Feedthrough AISI 303 (1.4305), AISI 304 (1.4301)

FKM (Viton®) Seal Bonnet - Gate, dynamic

FKM (Viton®) FKM (Viton®) Feedthrough

Mounting position any

Volume of pneumatic actuator 0.30 I / 0.010 ft³

Compressed air 5 - 7 bar / 73 - 102 psi

min. - max. overpressure

Compressed air connection M5 (10-32 UNF suitable)

Created by: MAEM	Release date: 2013-01-29	1 of 2
Modified by:	Release date:	276576EA



Product data sheet

Pendulum valve, Series 162, DN 200 (ID 8") Ordering No. 16246-TA21

Actuation time - closing 4 s

- opening 4 s

Weight 23 kg / 50.7 lbs


Behavior in case of compressed valve remains closed - Valve closed air pressure drop valve closes Valve open

Behavior in case of power failure - Valve closed depending on customer installation

Valve open depending on customer installation

Position indicator

Type Micro switch Voltage ≤ 50 V AC Current max. ≤ 1.2 A



Wiring diagram

Created by: MAEM	Release date: 2013-01-29	2 of 2
Modified by:	Release date:	276576EA