

Product data sheet

Pendulum valve, Series 162, DN 250 (ID 10") Ordering No. 16248-JA21

Description

JIS 250 Flange

Actuator - pneumatic, single acting, with closing spring (NC)

with position indicator

Feedthrough Rotary feedthrough

Technical data

< 1 · 10⁻⁹ mbar ls⁻¹ Leak rate Valve body $< 1 \cdot 10^{-9} \text{ mbar ls}^{-1}$

- Valve seat

1 · 10⁻⁸ mbar to 1.2 bar (abs) Pressure range

Differential pressure on the gate ≤ 1.2 bar Differential pressure at opening ≤ 5 mbar 21 700 ls⁻¹ Conductance (molecular flow)

Cycles until first service 200 000 (unheated and under clean conditions)

Temperature ≤ 120 °C Valve body (Maximum values: depending ≤ 80 °C Actuator - Position indicator ≤ 80 °C on operating conditions and

sealing materials)

 \leq 30 °C h⁻¹ Heating and cooling rate

Material Valve body, gate,

sealing ring EN AW-5083 (3.3547), EN AW-6082 (3.2315)

Feedthrough AISI 303 (1.4305), AISI 304 (1.4301)

FKM (Viton®) Seal Bonnet - Gate, dynamic

FKM (Viton®) FKM (Viton®) Feedthrough

Mounting position any

Volume of pneumatic actuator 0.35 I / 0.012 ft³

5 - 7 bar / 73 - 102 psiCompressed air

min. - max. overpressure

Compressed air connection M5 (10-32 UNF suitable)

Created by: MAEM	Release date: 2013-01-29	1 of 2
Modified by:	Release date:	266158EA



Product data sheet

Pendulum valve, Series 162, DN 250 (ID 10") Ordering No. 16248-JA21

Actuation time – closing 4 s

– opening 4 s

Weight 30 kg / 66.1 lbs


Behavior in case of compressed — Valve closed valve remains closed air pressure drop — Valve open valve closes

Behavior in case of power failure — Valve closed depending on customer installation

Valve open depending on customer installation

Position indicator

Type Micro switch Voltage $\leq 50 \text{ V AC}$ Current max. $\leq 1.2 \text{ A}$



Wiring diagram

Created by: MAEM	Release date: 2013-01-29	2 of 2
Modified by:	Release date:	266158EA