



VAT Vakuumventile AG
CH-9469 Haag, Schweiz

Product data sheet

Pendulum valve, Series 162, DN 320 (ID 12")
Ordering No. 16250-TA21-0001

Description

Flange	ASA-LP 320
Actuator	– pneumatic, single acting, with closing spring (NC) – with position indicator
Feedthrough	Rotary feedthrough

Technical data

Leak rate	– Valve body	$< 1 \cdot 10^{-9}$ mbar ls ⁻¹
	– Valve seat	$< 1 \cdot 10^{-9}$ mbar ls ⁻¹
Pressure range		$1 \cdot 10^{-8}$ mbar to 1.2 bar (abs)
Differential pressure on the gate		≤ 1.2 bar
Differential pressure at opening		≤ 5 mbar
Conductance (molecular flow)		32 600 ls ⁻¹
Cycles until first service		200 000 (unheated and under clean conditions)
Temperature	– Valve body	≤ 120 °C
(Maximum values: depending on operating conditions and sealing materials)	– Actuator	≤ 80 °C
	– Position indicator	≤ 80 °C
Heating and cooling rate		≤ 30 °C h ⁻¹
Material	– Valve body, gate, sealing ring	EN AW-5083 (3.3547), EN AW-6082 (3.2315)
	– Feedthrough	AISI 303 (1.4305), AISI 304 (1.4301)
Seal	– Bonnet	FKM (Viton®)
	– Gate, dynamic	FKM (Viton®)
	– Feedthrough	FKM (Viton®)
Mounting position		any
Volume of pneumatic actuator		0.55 l / 0.020 ft ³
Compressed air min. – max. overpressure		5 – 7 bar / 73 – 102 psi
Compressed air connection		M5 (10-32 UNF suitable)

Created by: MAEM	Release date: 2013-06-11	1 of 2
Modified by:	Release date:	602875EA



VAT Vakuumventile AG
CH-9469 Haag, Schweiz

Product data sheet


Pendulum valve, Series 162, DN 320 (ID 12")

Ordering No. 16250-TA21-0001

Actuation time	- closing	5 s
	- opening	5 s
Weight		56 kg / 123.5 lbs
Behavior in case of compressed air pressure drop	- Valve closed	valve remains closed
	- Valve open	valve closes
Behavior in case of power failure	- Valve closed	depending on customer installation
	- Valve open	depending on customer installation

Position indicator

Type	Micro switch
Voltage	≤ 50 V AC
Current max.	≤ 1.2 A



Wiring diagram