

Product data sheet Pendulum valve, Series 162, DN 350 (ID 14'') Ordering No. 16251-JH21

Description

Flange		JIS 350
Actuator		 pneumatic, single acting, with closing spring (NC) with position indicator
Feedthrough		Rotary feedthrough
Technical data		
Leak rate	Valve bodyValve seat	< 1 · 10 ⁻⁶ mbar Is ⁻¹ < 1 · 10 ⁻⁵ mbar Is ⁻¹
Pressure range		$1 \cdot 10^{-6}$ mbar to 1.2 bar (abs)
Differential pressure on the gate		≤ 1.2 bar
Differential pressure at opening		≤ 5 mbar
Conductance (molecular flow)		41 500 ls ⁻¹
Cycles until first service		200 000 (unheated and under clean conditions)
Temperature (Maximum values: depending on operating conditions and sealing materials)	Valve bodyActuatorPosition indicator	≤ 120 °C ≤ 80 °C ≤ 80 °C
Heating and cooling rate		\leq 30 °C h ⁻¹
Material	 Valve body, gate, sealing ring 	EN AW-6082 (3.2315), hard anodized
	 Feedthrough 	AISI 303 (1.4305), AISI 304 (1.4301)
Seal	– Bonnet – Gate, dynamic – Feedthrough	FKM (Viton [®]) FKM (Viton [®]) FKM (Viton [®])
Mounting position		any
Volume of pneumatic actuator		0.60 l / 0.021 ft ³
Compressed air min. – max. overpressure		5 – 7 bar / 73 – 102 psi
Compressed air connection		M5 (10-32 UNF suitable)

Created by: MAEM	Release date: 2013-02-15	1 of 2
Modified by:	Release date:	298088EA




Product data sheet Pendulum valve, Series 162, DN 350 (ID 14'') Ordering No. 16251-JH21

Actuation time	– closing – opening	5 s 5 s
Weight		65 kg / 143.3 lbs
Behavior in case of compressed air pressure drop	– Valve closed – Valve open	valve remains closed valve closes
Behavior in case of power failure	 Valve closed Valve open 	depending on customer installation depending on customer installation

Position indicator

Туре	Micro switch
Voltage	\leq 50 V AC
Current max.	\leq 1.2 A



Wiring diagram

Created by: MAEM	Release date: 2013-02-15	2 of 2
Modified by:	Release date:	298088EA