



VAT Vakuumventile AG  
CH-9469 Haag, Schweiz

## Product data sheet

**Pendulum valve, Series 162, DN 400 (ID 16'')**  
**Ordering No. 16252-JA21**

### Description

Flange	JIS 400
Actuator	– pneumatic, single acting, with closing spring (NC) – with position indicator
Feedthrough	Rotary feedthrough

### Technical data

Leak rate	– Valve body	$< 1 \cdot 10^{-9}$ mbar ls <sup>-1</sup>
	– Valve seat	$< 1 \cdot 10^{-9}$ mbar ls <sup>-1</sup>
Pressure range		$1 \cdot 10^{-8}$ mbar to 1.2 bar (abs)
Differential pressure on the gate		$\leq 1.2$ bar
Differential pressure at opening		$\leq 5$ mbar
Conductance (molecular flow)		61 000 ls <sup>-1</sup>
Cycles until first service		200 000 (unheated and under clean conditions)
Temperature	– Valve body	$\leq 120$ °C
(Maximum values: depending on operating conditions and sealing materials)	– Actuator	$\leq 80$ °C
	– Position indicator	$\leq 80$ °C
Heating and cooling rate		$\leq 30$ °C h <sup>-1</sup>
Material	– Valve body, gate, sealing ring	EN AW-5083 (3.3547), EN AW-6082 (3.2315)
	– Feedthrough	AISI 303 (1.4305), AISI 304 (1.4301)
Seal	– Bonnet	FKM (Viton®)
	– Gate, dynamic	FKM (Viton®)
	– Feedthrough	FKM (Viton®)
Mounting position		any
Volume of pneumatic actuator		0.65 l / 0.023 ft <sup>3</sup>
Compressed air		5 – 7 bar / 73 – 102 psi
min. – max. overpressure		
Compressed air connection		M5 (10-32 UNF suitable)

Created by: MAEM	Release date: 2014-07-07	1 of 2
Modified by:	Release date:	<b>289750EA</b>



VAT Vakuumventile AG  
CH-9469 Haag, Schweiz

## Product data sheet

**Pendulum valve, Series 162, DN 400 (ID 16")**  
**Ordering No. 16252-JA21**

Actuation time	- closing	5.5 s
	- opening	5.5 s
Weight		76 kg / 167.6 lbs
Behavior in case of compressed air pressure drop	- Valve closed	valve remains closed
	- Valve open	valve closes
Behavior in case of power failure	- Valve closed	depending on customer installation
	- Valve open	depending on customer installation

### Position indicator

Type	Micro switch
Voltage	≤ 50 V AC / DC
Current max.	≤ 1.2 A

