

Product data sheet

Large pendulum valves Series 168, DN 400 (16") Ordering No. 16852-PA28-0002

Description

Flange		ISO-F 400
Actuator		3-position pneumatic, double acting – with position indicator
Feedthrough		Rotary feedthrough
Technical data		
Leak rate	– Valve body – Valve seat	< 1 · 10 ⁻⁹ mbar Is ⁻¹ < 1 · 10 ⁻⁹ mbar Is ⁻¹
Pressure range		1 · 10 ⁻⁸ mbar to 1.2 bar (abs)
Differential pressure on the gate		≤ 1.2 bar
Differential pressure at opening		≤ 30 mbar
Conductance (molecular flow)		50 000 ls ⁻¹
Minimum conductance (molecular flow) 3 rd position		150 ls ⁻¹
Cycles until first service		100 000
Temperature (Maximum values: depending on operating conditions and sealing materials)	 Valve body Actuator Position indicator 	≤ 120 °C ≤ 80 °C ≤ 80 °C
Heating and cooling rate		≤ 30 °C h ⁻¹
Material	– Valve body – Mechanics – Gate – Feedthrough	EN AC-42100 (3.2371), EN AW-6082 (3.2315) EN AC-42100 (3.2371) EN AW-6082 (3.2315) EN AW-6082 (3.2315), AISI 303 (1.4305)
Seal	– Bonnet – Gate – Actuator – Feedthrough	FKM (Viton [®]) FKM (Viton [®]) FKM (Viton [®]), NBR FKM (Viton [®])
Mounting position		any
Volume of pneumatic actuator		2 I / 0.07 ft ³
Compressed air min. – max. overpressure		5 – 7 bar / 73 – 102 psi
Compressed air connection		1⁄8" ISO / NPT

 Created by: LBI
 Release date: 31.08.2017
 1/2

 Modified by:
 Release date:
 249126EC



Product data sheet

Large pendulum valves Series 168, DN 400 (16") Ordering No. 16852-PA28-0002

Weight

Behavior in case of compressed air pressure drop

Behavior in case of power failure

– opening
 Valve closed Valve open During actuation
 Valve closed Valve open During actuation

- closing


12 s 12 s

85 kg / 187 lbs

valve remains closed undefined undefined

valve remains closed valve closes valve closes

Туре	Micro switch
Voltage	≤ 50 V AC / DC
Current max.	≤ 3 A



Wiring diagram

Created by: LBI	Release date: 31.08.2017	2/2
Modified by:	Release date:	249126EC