




VAT Vakuumventile AG  
CH-9469 Haag, Schweiz

## PRODUCT DATA SHEET No. 229794EG

**Vatterfly valve, Series 20, DN 63-200 (ID 2½'' - 8'')**

**Ordering No:**                    **20 . . . - . . 14**



### Description

Flanges and body shape                    according to dimensional drawing  
Actuator                                        pneumatic, double acting  
Feedthrough                                 rotary feedthrough

### Technical data

Leak rate:  
     - To the outside                                 $< 1 \cdot 10^{-9}$  mbar ls<sup>-1</sup>  
     - Valve seat                                       $< 1 \cdot 10^{-9}$  mbar ls<sup>-1</sup>  
 Pressure range                                 $1 \cdot 10^{-8}$  mbar to 2 bar, abs  
 Differential pressure on the plate             $\leq 1.2$  bar in opening direction  
     $\leq 1.6$  bar in closing direction  
 Differential pressure at opening             $\leq 0.5$  bar  
 Admissible temperature:                    0 - 120°C  
 Heating and cooling rate:                     $\leq 40^\circ\text{C h}^{-1}$   
 Cycles until first service                    100,000  
    - under clean vacuum conditions  
    - at a temperature between 0 and 80°C  
 Life cycle                                        500,000

		A: Aluminum body	E: Stainless Steel body
Material:	- valve body	Al Mg Si 1	1.4301
	- actuator	Aluminum	Aluminum
	- valve plate	Al Mg Si 1	1.4301
Seal	- bonnet seal	VITON®	VITON®
	- plate seal	VITON®	VITON®
	- pneumatic seals	VITON®	VITON®

Editor: M. Kienreich	Date: 03-10-22	Page 1 of 2
Replaced by	Replacement for	<b>229794EG</b>
Modification No.	Modification No.	



VAT Vakuumventile AG  
CH-9469 Haag, Schweiz

## PRODUCT DATA SHEET No. 229794EG

### Vatterfly valve, Series 20, DN 63-200 (ID 2½'' - 8'')

Mounting position	any
Action at power failure	depending on installation of customer
Action at compressed air failure	no change
Compressed air pressure for pneumatics	4 - 7 bar / 60 - 100 psi
Compressed air connection	M 5 female (10/32 UNF suitable)

Diameter code	36	38	40	44	46
Diameter	63 mm 2½"	80 mm 3"	100 mm 4"	160 mm 6"	200 mm 8"
Volume of air cylinder	0.04 l 0.0014 ft <sup>3</sup>	0.08 l 0.003 ft <sup>3</sup>	0.08 l 0.003 ft <sup>3</sup>	0.13 l 0.0045 ft <sup>3</sup>	0.3 l 0.01 ft <sup>3</sup>
Opening / Closing time	0.4 s	0.8 s	0.8 s	1.4 s	1.8 s
Molecular flow conductance	550 ls <sup>-1</sup>	700 ls <sup>-1</sup>	1400 ls <sup>-1</sup>	4000 ls <sup>-1</sup>	7500 ls <sup>-1</sup>
Molecular flow conductance (extended body)	450 ls <sup>-1</sup>	600 ls <sup>-1</sup>	1050 ls <sup>-1</sup>	2550 ls <sup>-1</sup>	4700 ls <sup>-1</sup>
Weight (standard Aluminum body) 203 . . . A . .	2.3 kg 5.1 lbs	3.8 kg 8.4 lbs	4 kg 8.8 lbs	7.4 kg 16.3 lbs	16.1 kg 35.5 lbs
Weight (standard Stainless Steel body) 203 . . . E . .	4.6 kg 10.1 lbs	7.5 kg 16.5 lbs	8 kg 17.6 lbs	15.6 kg 34.4 lbs	34.2 kg 75.4 lbs
Weight (extended Aluminum body) 204 . . . A . .	2.5 kg 5.5 lbs	4.2 kg 9.3 lbs	4.7 kg 10.4 lbs	9.7 kg 21.4 lbs	21.3 kg 47 lbs
Weight (extended Stainless Steel body) 204 . . . E . .	5.3 kg 11.7 lbs	8.5 kg 18.7 lbs	10.1 kg 22.3 lbs	22.3 kg 49.2 lbs	20.8 kg 45.9 lbs

Editor: M. Kienreich	Date: 03-10-22	Page 2 of 2
Replaced by	Replacement for	<b>229794EG</b>
Modification No.	Modification No.	