



VAT Vakuumventile AG
CH-9469 Haag, Schweiz

Product data sheet

Diaphragm valve
Series 220, DN 16 (ID 5/8")
Ordering No. 22024-KA01-0003

Description

Flange	ISO-KF 16
Actuator	Manual actuator
Feedthrough	Diaphragm

Technical data

Leak rate	- Valve body	$< 1 \cdot 10^{-9} \text{ mbar ls}^{-1}$
	- Valve seat	$< 1 \cdot 10^{-9} \text{ mbar ls}^{-1}$
Pressure range		$1 \cdot 10^{-7} \text{ mbar to 5 bar (abs)}$
Differential pressure on the plate		$\leq 5 \text{ bar in either direction}$
Conductance (molecular flow)		2 ls^{-1}
Cycles until first service		20 000
Temperature (Maximum values: depending on operating conditions and sealing materials)	- Valve body	$\leq 100 \text{ }^\circ\text{C}$
	- Hand wheel	$\leq 50 \text{ }^\circ\text{C}$
	- diaphragm	$\leq 100 \text{ }^\circ\text{C}$
Material	- Valve body	Aluminum (AlMg Si)
	- Hand wheel	POM
Seal	- diaphragm	FKM (Viton [®])
Mounting position		any

Created by: EMI	Release date: 10.03.2015	1/1
Modified by:	Release date:	790414EA