



VAT Vakuumventile AG  
CH-9469 Haag, Schweiz

## Product data sheet

### Valve mechanism (lock)

### Series 230, DN 16 (5/8")

Ordering No. 23024-KA01-0001 and 23024-KEPS-0002

#### Description

Flange	ISO-KF 16
Actuator	Manual actuator
Feedthrough	Shaft feedthrough

#### Technical data

Leak rate	- Valve mechanism	$< 1 \cdot 10^{-8}$ mbar ls <sup>-1</sup>
	- Pump-out port	$< 1 \cdot 10^{-9}$ mbar ls <sup>-1</sup>
Pressure range		$1 \cdot 10^{-8}$ mbar to 2.5 bar (abs)
Differential pressure at opening		$\leq 1$ bar
Temperature (Maximum values: depending on operating conditions and sealing materials)	- Valve mechanism	$\leq 150$ °C
	- Hand wheel	$\leq 50$ °C
	- Pump-out port	$\leq 150$ °C
Material	- Valve mechanism	EN AW-6060 (3.3206)
	- Shaft	AISI 304 (1.4301)
	- Pump-out port body	AISI 304 (1.4301)
	- Pump-out port plate	AISI 304 (1.4301)
Seal valve mechanism	- Bonnet	FKM (Viton®)
	- Feedthrough	FKM (Viton®)
Seal pump-out port	- Plate	FKM (Viton®)
Unobstructed flow diameter	- Pump-out port	2.5mm / 0.10 inch
Mounting position		any
Weight	- Valve mechanism	0.35kg / 0.77lbs
	- Pump-out port	0.05kg / 0.11lbs

Created by: AMT	Release date: 14.11.2018	1/1
Modified by:	Release date:	<b>906571EA</b>