



VAT Vakuumventile AG
CH-9469 Haag, Schweiz

Product data sheet

Valve mechanism (lock)

Series 230, DN 40 (1 1/2")

Ordering No. 23032-KA01-0001 and 23032-KEPS-0002

Description

Flange	ISO-KF 40
Actuator	Manual actuator
Feedthrough	Shaft feedthrough

Technical data

Leak rate	- Valve mechanism	$< 1 \cdot 10^{-8}$ mbar ls ⁻¹
	- Pump-out port	$< 1 \cdot 10^{-9}$ mbar ls ⁻¹
Pressure range		$1 \cdot 10^{-8}$ mbar to 2.5 bar (abs)
Differential pressure at opening		≤ 1 bar
Temperature (Maximum values: depending on operating conditions and sealing materials)	- Valve mechanism	≤ 150 °C
	- Hand wheel	≤ 50 °C
	- Pump-out port	≤ 150 °C
Material	- Valve mechanism	EN AW-6060 (3.3206)
	- Shaft	AISI 304 (1.4301)
	- Pump-out port body	AISI 304 (1.4301)
	- Pump-out port plate	AISI 304 (1.4301)
Seal valve mechanism	- Bonnet	FKM (Viton®)
	- Feedthrough	FKM (Viton®)
Seal pump-out port	- Plate	FKM (Viton®)
Unobstructed flow diameter	- Pump-out port	18mm / 0.71 inch
Mounting position		any
Weight	- Valve mechanism	1.9kg / 4.19lbs
	- Pump-out port	0.25kg / 0.55lbs

Created by: EMI	Release date: 06.11.2018	1/1
Modified by:	Release date:	906573EA