



VAT Vakuumventile AG
CH-9469 Haag, Schweiz

Product data sheet No. 243252ED

Vacuum Angle Valve, Series 244, DN 25 (ID 1 ")

Ordering No. 24428-KA41 or 24428-KE41

Description

Flanges	ISO-KF25
Actuator	- pneumatic, single acting with closing spring - with solenoid - with position indicator "open" and "closed"
Feedthrough	shaft feedthrough

Technical data

Leak rate	- body & valve seat	$< 1 \cdot 10^{-9}$ mbar ls ⁻¹
Molecular flow conductance		14 ls ⁻¹
Pressure range		$1 \cdot 10^{-7}$ mbar to 5 bar, abs
Differential pressure on the plate:		
- in opening direction		≤ 2 bar
- in closing direction		≤ 5 bar
Differential pressure at opening:		
- in opening direction		≤ 1 bar
- in closing direction		≤ 1 bar
		≤ 3 bar with reduced cycle lifetime (min. 450 000) (compressed air pressure > 5 bar required to open)
Closing time		≤ 0,2 sec.
Admissible temperature:		
- valve body, actuator		0°C - 120°C
- solenoid		0°C - 80°C
- position indicator		0°C - 80°C (option 120°C)
Cycles until first service		3 million (T _{max} 80°C, differential pressure max. 1 bar)
Material:		
- valve body	24428-KA41	24428-KE41
- pneumatic actuator	Aluminum (AlMgSi)	Stainless Steel (AISI 304)
- valve plate	Aluminum	Aluminum
- feedthrough	AISI 316L	AISI 316L
- bonnet & plate seal	Aluminum	Aluminum
- actuator o-rings	Viton	Viton
	Viton	Viton
Weight		0,5 kg / 1,102 lbs 0,6 kg / 1,322 lbs
Mounting position		any
Volume of air cylinder		0,011 l / 0,0004 ft ³
Compressed air pressure for pneumatic		4 - 8 bar / 60 - 115 psi
Compressed air connection		M5 female (option others)
Position indicator: contact rating		
- Voltage		≤ 50V AC / DC
- Current		≤ 0.1A
- Power		≤ 1 W
Solenoid		24V / DC (option others)

Created by: C. Baur	Release date: 2005.03.16	Page 1 of 2
Modified by::	Release date:	243252ED



VAT Vakuumventile AG
CH-9469 Haag, Schweiz

Product data sheet No. 243252ED

Vacuum Angle Valve, Series 244, DN 25 (ID 1 ")

Ordering No. 24428-KA41 or 24428-KE41

