



VAT Vakuumventile AG  
CH-9469 Haag, Schweiz

## Product data sheet No. 243621EB

**Vacuum Angle Valve, Series 244, DN 40 (ID 1 1/2 ")**

**Ordering No. 24432-KA11 or 24432-KE11**

### Description

Flanges	ISO-KF40
Actuator	- pneumatic, single acting with closing spring - without solenoid - without position indicator
Feedthrough	shaft feedthrough

### Technical data

Leak rate	- body & valve seat	$< 1 \cdot 10^{-9}$ mbar ls <sup>-1</sup>
Molecular flow conductance		45 ls <sup>-1</sup>
Pressure range		$1 \cdot 10^{-7}$ mbar to 5 bar, abs
Differential pressure on the plate:		
- in opening direction		$\leq 2$ bar
- in closing direction		$\leq 5$ bar
Differential pressure at opening:		
- in opening direction		$\leq 1$ bar
- in closing direction		$\leq 1$ bar
		$\leq 3$ bar with reduced cycle lifetime (min. 450 000) (compressed air pressure > 5 bar required to open)
Closing time		$\leq 0,55$ sec.
Admissible temperature:	- valve body, actuator	0°C - 120°C
Cycles until first service		3 million (T <sub>max</sub> 80°C, differential pressure max. 1 bar)
Material:		
	- valve body	<b>24432-KA11</b> Aluminum (AlMgSi) <b>24432-KE11</b> Stainless Steel (AISI 304)
	- pneumatic actuator	Aluminum
	- valve plate	AISI 316L
	- feedthrough	Aluminum
	- bonnet & plate seal	Viton
	- actuator o-rings	Viton
Weight		0,97 kg / 2,138 lbs      1,13 kg / 2,491 lbs
Mounting position		any
Volume of air cylinder		0,035 l / 0,0012 ft <sup>3</sup>
Compressed air pressure for pneumatic		4 - 8 bar / 60 - 115 psi
Compressed air connection		M5 female (option others)

Created by: C. Baur	Release date: 2005.03.16	Page 1 of 1
Modified by::	Release date:	<b>243621EB</b>