



VAT Vakuumventile AG  
CH-9469 Haag, Schweiz

## Product data sheet

**Vacuum angle valve, Series 244, DN 63 (ID 2 1/2")**  
**Ordering No. 24436-QE21-0003**

### Description

Flange	ISO-K 63
Actuator	Pneumatic, single acting with closing spring – without solenoid valve – with position indicator “open” and “closed”
Feedthrough	Shaft feedthrough

### Technical data

Leak rate	– Valve body – Valve seat	$< 1 \cdot 10^{-9}$ mbar ls <sup>-1</sup> $< 1 \cdot 10^{-9}$ mbar ls <sup>-1</sup>
Pressure range		$1 \cdot 10^{-7}$ mbar to 5 bar (abs)
Differential pressure on the plate	– In opening direction – In closing direction	$\leq 2$ bar $\leq 4$ bar
Differential pressure at opening		$\leq 1$ bar
Conductance (molecular flow)		160 ls <sup>-1</sup>
Closing time		$\leq 0.7$ sec.
Cycles until first service (T <sub>max</sub> 80°C, under clean conditions)		3 million
Temperature (Maximum values: depending on operating conditions and sealing materials)	– Valve body – Actuator – Position indicator	$\leq 150$ °C $\leq 120$ °C $\leq 80$ °C
Material	– Valve body – Actuator – Plate – Shaft feedthrough	AISI 316L (1.4404) Aluminum AISI 316L (1.4435 ESU) AISI 304 (1.4301)
Seal	– Bonnet O-ring – Plate O-ring – Actuator O-ring	FKM (Viton®) FKM (Viton®) FKM (Viton®)
Weight		1.7 kg / 3.75 lbs
Mounting position		any
Volume of pneumatic actuator		0.112 l / 0.0040 ft <sup>3</sup>
Compressed air min. – max. overpressure		4 – 8 bar / 60 – 115 psi
Compressed air connection		female 1/8" (ISO/NPT)

Created by: R. Walser	Release date: 2013-07-24	1 of 2
Modified by:	Release date:	<b>603470EA</b>



VAT Vakuumventile AG  
CH-9469 Haag, Schweiz


## Product data sheet

**Vacuum angle valve, Series 244, DN 63 (ID 2 1/2")**  
**Ordering No. 24436-QE21-0003**

### Electrical connections

#### Position indicator

Type	Micro switch
Voltage	≤ 50 V AC / DC
Current	5 – 100 mA
Short circuit protected	No
Connection	Cable, 4 wires
Cable length	500 mm
Cable cross section	0.25 mm <sup>2</sup>



Wiring diagram