

Product data sheet Vacuum angle valve Series 244, DN 100 (ID 4'') Ordering No. 24440-QA14-0001

Description

Flange		ISO-K 100
Actuator		Pneumatic, double acting – without solenoid valve – without position indicator
Feedthrough		Shaft feedthrough
Technical data		
Leak rate (static)	– Valve body – Valve seat	< $1 \cdot 10^{-9}$ mbar ls ⁻¹ < $1 \cdot 10^{-9}$ mbar ls ⁻¹
Pressure range		$1 \cdot 10^{-7}$ mbar to 2 bar (abs)
Differential pressure on the plate	 In opening direction In closing direction 	≤ 1.2 bar ≤ 2 bar
Differential pressure at opening		≤ 1 bar
Conductance (molecular flow)		440 ls ⁻¹
Actuation time	 Closing Opening 	≤ 1 sec. ≤ 1 sec.
Cycles until first service (Tmax 80°C, under clean conditions)		2 million
Temperature (Maximum values: depending on operating conditions and sealing materials)	 Valve body Actuator 	≤ 150 °C ≤ 120 °C
Material	– Valve body – Actuator – Plate – Shaft feedthrough	Aluminum (EN AC-42000) Aluminum Aluminum (EN AW 6082) Aluminum (EN AW 6082)
Seal	 Bonnet O-ring Plate O-ring Feedthrough O-ring Actuator O-ring 	FKM (Viton®) FKM (Viton®) FKM (Viton®) FKM (Viton®)
Weight		8 kg / 17.5 lbs
Mounting position		any
Volume of pneumatic actuator		0.3 I / 0.01 ft ³
Compressed air min. – max. overpressure		4.5 – 7 bar / 65 – 102 psi
Compressed air connection		1∕₃" ISO/NPT female
Behavior in case of compressed air pressure drop	 Valve closed Valve opened During actuation 	depending on customer installation depending on customer installation depending on customer installation

Created by: DIC	Release date: 15.04.2016	1/2
Modified by:	Release date:	603620EB



Product data sheet

Vacuum angle valve Series 244, DN 100 (ID 4'') Ordering No. 24440-QA14-0001

Behavior in case of power failure - Valve closed

- Valve closedValve opened
- During actuation

depending on customer installation depending on customer installation depending on customer installation

Created by: DIC	Release date: 15.04.2016	2/2
Modified by:	Release date:	603620EB