



VAT Vakuumventile AG
CH-9469 Haag, Schweiz

Product data sheet

Vacuum angle valve
Series 244, DN 100 (ID 4'')
Ordering No. 24440-QA34-0001

Description

Flange	ISO-K 100
Actuator	Pneumatic, double acting – with solenoid valve – without position indicator
Feedthrough	Shaft feedthrough

Technical data

Leak rate (static)	– Valve body – Valve seat	$< 1 \cdot 10^{-9}$ mbar ls ⁻¹ $< 1 \cdot 10^{-9}$ mbar ls ⁻¹
Pressure range		$1 \cdot 10^{-7}$ mbar to 2 bar (abs)
Differential pressure on the plate	– In opening direction – In closing direction	≤ 1.2 bar ≤ 2 bar
Differential pressure at opening		≤ 1 bar
Conductance (molecular flow)		440 ls ⁻¹
Actuation time	– Closing – Opening	≤ 1 sec. ≤ 1 sec.
Cycles until first service (Tmax 80°C, under clean conditions)		2 million
Temperature (Maximum values: depending on operating conditions and sealing materials)	– Valve body – Actuator – Solenoid valve	≤ 150 °C ≤ 120 °C ≤ 50 °C
Material	– Valve body – Actuator – Plate – Shaft feedthrough	Aluminum (EN AC-42000) Aluminum Aluminum (EN AW 6082) Aluminum (EN AW 6082)
Seal	– Bonnet O-ring – Plate O-ring – Feedthrough O-ring – Actuator O-ring	FKM (Viton®) FKM (Viton®) FKM (Viton®) FKM (Viton®)
Weight		8 kg / 17.5 lbs
Mounting position		any
Volume of pneumatic actuator		0.3 l / 0.01 ft ³
Compressed air min. – max. overpressure		4.5 – 7 bar / 65 – 102 psi
Compressed air connection		G $\frac{1}{8}$ " female
Behavior in case of compressed air pressure drop	– Valve closed – Valve opened – During actuation	depending on customer installation depending on customer installation depending on customer installation

Created by: DIC	Release date: 15.04.2016	1/2
Modified by:	Release date:	603617EB



VAT Vakuumventile AG
CH-9469 Haag, Schweiz

Product data sheet

Vacuum angle valve
Series 244, DN 100 (ID 4'')
Ordering No. 24440-QA34-0001

Behavior in case of power failure

- Valve closed valve remains closed and leaktight
- Valve opened valve closes leaktight
- During actuation valve closes leaktight

Electrical connection


Solenoid valve

Type 5/2 way

Voltage See label on Solenoid

Connection type plug, male M8x1

Additional feature LED orange; overvoltage protection; adjustable emergency operation; silencer



Wiring diagram

Created by: DIC	Release date: 15.04.2016	2/2
Modified by:	Release date:	603617EB