



VAT Vakuumventile AG
CH-9469 Haag, Schweiz

Product data sheet

Vacuum Inline valve, Series 245, DN 25 (ID 1")
Ordering No. 24528-KA11-0001

Description

Flange	ISO-KF 25
Actuator	Pneumatic, single acting with closing spring – without solenoid valve – without position indicator
Feedthrough	Shaft feedthrough

Technical data

Leak rate	– Valve body – Valve seat	$< 1 \cdot 10^{-9}$ mbar ls ⁻¹ $< 1 \cdot 10^{-9}$ mbar ls ⁻¹
Pressure range		$1 \cdot 10^{-7}$ mbar to 5 bar (abs)
Differential pressure on the plate	– In opening direction – In closing direction	≤ 2 bar ≤ 5 bar
Differential pressure at opening		≤ 1 bar
Conductance (molecular flow)		14 ls ⁻¹
Closing time		≤ 0.20 sec.
Cycles until first service (Tmax 80°C, under clean conditions)		3 million
Temperature (Maximum values: depending on operating conditions and sealing materials)	– Valve body – Actuator	≤ 150 °C ≤ 120 °C
Material	– Valve body – Actuator – Plate – Feedthrough	Aluminum (EN AW-6060) Aluminum AISI 316L (1.4435 ESU) Stainless steel
Seal	– Bonnet O-ring – Plate O-ring – Actuator O-ring – Feedthrough O-ring	FKM (Viton®) FKM (Viton®) FKM (Viton®) FKM (Viton®)
Weight		0.41 kg / 0.90 lbs
Mounting position		Any
Volume of pneumatic actuator		0.011 l / 0.0004 ft ³
Compressed air min. – max. overpressure		4 – 8 bar / 58 – 116 psi
Compressed air connection		M5 female (10-32 UNF suitable)

Created by: A. Rietzler	Release date: 2013-11-08	1 of 1
Modified by:	Release date:	258456EC