



VAT Vakuumventile AG
CH-9469 Haag, Schweiz

Product data sheet

Vacuum inline valve
Series 245, DN 40 (ID 1 1/2")
Ordering No. 24532-KE01-0001

Description

Flange	ISO-KF 40
Actuator	Manual actuator
Feedthrough	Shaft feedthrough

Technical data

Leak rate	- Valve body	$< 1 \cdot 10^{-9}$ mbar ls ⁻¹
	- Valve seat	$< 1 \cdot 10^{-9}$ mbar ls ⁻¹
Pressure range		$1 \cdot 10^{-7}$ mbar to 5 bar (abs)
Differential pressure on the plate	- In opening direction	≤ 2 bar
	- In closing direction	≤ 5 bar
Differential pressure at opening		≤ 1 bar
Conductance (molecular flow)		45 ls ⁻¹
Cycles until first service (Tmax 80 °C, under clean conditions)		10 000
Temperature (Maximum values: depending on operating conditions and sealing materials)	- Valve body	≤ 150 °C
	- Hand wheel	≤ 120 °C
Material	- Valve body	Stainless Steel (AISI 304)
	- Hand wheel	Plastic
	- Plate	AISI 316L (1.4435 ESU)
	- Feedthrough	Stainless Steel
Seal	- Bonnet O-ring	FKM (Viton [®])
	- Plate O-ring	FKM (Viton [®])
	- Feedthrough O-ring	FKM (Viton [®])
Weight		1.4 kg / 3.08 lbs
Mounting position		any

Created by: WARO	Release date: 26.03.2014	1/1
Modified by:	Release date:	742547EA