



VAT Vakuumventile AG
CH-9469 Haag, Schweiz

Product data sheet No. 276858EA

Vacuum Inline Valve, Series 245, DN 80 (ID 3 ")

Ordering No. 24538-QA31

Description

Flanges	ISO-K80
Actuator	- pneumatic, single acting with closing spring - with solenoid - without position indicator
Feedthrough	shaft feedthrough

Technical data

Leak rate	- body & valve seat	$< 1 \cdot 10^{-9}$ mbar ls ⁻¹
Molecular flow conductance		200 ls ⁻¹
Pressure range		$1 \cdot 10^{-7}$ mbar to 4 bar, abs
Differential pressure on the plate:		
- in opening direction		$\leq 1,2$ bar
- in closing direction		≤ 4 bar
Differential pressure at opening:		
- in opening direction		≤ 1 bar
- in closing direction		≤ 1 bar
		≤ 3 bar with reduced cycle lifetime (min. 450 000) (compressed air pressure > 5 bar required to open)
Closing time		$\leq 0,7$ sec.
Admissible temperature:		
	- valve body, actuator	0°C - 120°C
	- solenoid	0°C - 80°C
Cycles until first service		3 million (T_{max} 80°C, differential pressure max. 1 bar)
Material:		24538-QA31
	- valve body	Aluminum (G-AISI)
	- pneumatic actuator	Aluminum
	- valve plate	AISI 316L
	- feedthrough	Aluminum
	- bonnet & plate seal	Viton
	- actuator o-rings	Viton
Weight		3,70 kg / 8,159 lbs
Mounting position		any
Volume of air cylinder		0,112 l / 0,0040 ft ³
Compressed air pressure for pneumatic		4 - 8 bar / 60 - 115 psi
Compressed air connection		R1/8" female (option others)
Solenoid		24V / DC (option others)

Created by: S. Vetter	Release date: 2008-09-04	Page 1 of 2
Modified by::	Release date:	276858EA



VAT Vakuumventile AG
CH-9469 Haag, Schweiz

Product data sheet No. 276858EA


Vacuum Inline Valve, Series 245, DN 80 (ID 3'')

Ordering No. 24538-QA31

Electrical connection Elektrischer Anschluss Branchement électrique

MV

Coil solenoid valve
Spule Steuerventil
Bobine de l'électrovanne



Created by: S. Vetter

Release date: 2008-09-04

Page 2 of 2

Modified by::

Release date:

276858EA