

## **Product data sheet**

## HV angle valve Series 264, DN 25 (ID 1") Ordering No. 26428-KE11-0001

**Description** 

Flange ISO-KF 25

Actuator Pneumatic, single acting with closing spring

without solenoid valvewithout position indicator

Feedthrough Bellows

**Technical data** 

Leak rate - Valve body  $< 1 \cdot 10^{-9} \text{ mbar Is}^{-1}$ 

- Valve seat  $< 1 \cdot 10^{-9}$  mbar ls<sup>-1</sup>

Pressure range  $1 \cdot 10^{-8}$  mbar to 5 bar (abs)

Differential pressure on the plate - In opening direction  $\leq 2$  bar

In closing direction ≤ 5 bar

Differential pressure at opening ≤ 1 bar

Conductance (molecular flow) 14 ls<sup>-1</sup>

Closing time ≤ 0.2 sec.

Cycles until first service 3 million

(Tmax 80 °C, under clean

conditions)

Temperature – Valve body ≤ 150 °C (Maximum values: depending – Actuator ≤ 120 °C

on operating conditions and

sealing materials)

Material – Valve body AISI 304 (1.4301)

Actuator Aluminum

– Plate AISI 316L (1.4404)

- Bellows AISI 316L (1.4404, 1.4435) AISI 316 Ti (1.4571)

Seal – Bonnet O-ring FKM (Viton®)

Plate O-ring
 Actuator O-ring
 FKM (Viton®)
 FKM (Viton®)

Weight 0.50 kg / 1.10 lbs

Mounting position any

Volume of pneumatic actuator 0.011 I / 0.0004 ft<sup>3</sup>

Compressed air 4-8 bar / 58-116 psi

min. - max. overpressure

Compressed air connection M5 female (10-32 UNF suitable)

Created by: WARO	Release date: 22.04.2014	1/2
Modified by:	Release date:	746422EA



## **Product data sheet**

HV angle valve Series 264, DN 25 (ID 1") Ordering No. 26428-KE11-0001

Behavior in case of compressed air pressure drop

 Valve closed Valve opened valve remains closed and leaktight

During actuation

valve closes leaktight valve closes leaktight

Behavior in case of power failure

 Valve closed Valve opened depending on customer installation depending on customer installation

<ul> <li>During actuation depending on customer installation</li> </ul>			
	<ul> <li>During actuation</li> </ul>	depending on customer in	nstallatior

Created by: WARO	Release date: 22.04.2014	2/2
Modified by:	Release date:	746422EA