

Product data sheet

HV angle valve Series 264, DN 63 (ID 2 1/2") Ordering No. 26436-QA11-0002

Description

ISO-K 63 Flange

Actuator Pneumatic, single acting with closing spring

> - without solenoid valve - without position indicator

Feedthrough **Bellows**

Technical data

 $< 1 \cdot 10^{-9} \, \text{mbar Is}^{-1}$ - Valve body Leak rate $< 1 \cdot 10^{-9} \text{ mbar Is}^{-1}$

Valve seat

 $1 \cdot 10^{-8}$ mbar to 4 bar (abs) Pressure range

Differential pressure on the plate - In opening direction ≤ 1.2 bar

- In closing direction ≤ 4 bar

Differential pressure at opening ≤ 1 bar

Conductance (molecular flow) 160 ls⁻¹

Closing time ≤ 0.7 sec.

Cycles until first service

(Tmax 80°C, under clean

conditions)

Temperature Valve body ≤ 150 °C - Actuator ≤ 120 °C

(Maximum values: depending on operating conditions and

sealing materials)

Material Aluminum (EN AW-6060) Valve body

> Actuator Aluminum

- Plate AISI 316L (1.4435 ESU)

3 million

- Bellows AISI 316L (1.4404, 1.4435), AISI 316 Ti (1.4571)

Seal Bonnet O-ring FKM (Viton®)

- Plate O-ring FKM (Viton®) - Actuator O-ring FKM (Viton®)

Weight 3.6kg / 7.936 lbs

Mounting position any

Volume of pneumatic actuator 0.112 I / 0.0040 ft3

4 - 8 bar / 60 - 115 psi Compressed air

min. - max. overpressure

Compressed air connection Female 1/8" (ISO/NPT)

Created by: WARO	Release date: 10.06.2014	1/2
Modified by:	Release date:	753420EA



Product data sheet

HV angle valve Series 264, DN 63 (ID 2 1/2") Ordering No. 26436-QA11-0002

Behavior in case of compressed

air pressure drop

- Valve closed valve remains closed and leaktight

Valve opened valve closes leaktightDuring actuation valve closes leaktight

Behavior in case of power failure

Valve closedValve openedDuring actuation

valve remains closed and leaktight depending on customer installation depending on customer installation

Created by: WARO	Release date: 10.06.2014	2/2
Modified by:	Release date:	753420EA