

## **Product data sheet**

HV angle valve Series 264, DN 100 (ID 4'') Ordering No. 26440-QA11-0001

## **Description**

Flange ISO-K 100

Actuator Pneumatic, single acting with closing spring

without solenoid valvewithout position indicator

Feedthrough Bellows

**Technical data** 

Leak rate - Valve body  $< 1 \cdot 10^{-9}$  mbar Is<sup>-1</sup> - Valve seat  $< 1 \cdot 10^{-9}$  mbar Is<sup>-1</sup>

Pressure range  $1 \cdot 10^{-8}$  mbar to 2 bar (abs)

Differential pressure on the plate - In opening direction  $\le$  1.2 bar

- In closing direction  $\leq 2$  bar

Differential pressure at opening ≤ 1 bar [1 bar with reduced number of cycles]

Conductance (molecular flow) 440 ls<sup>-1</sup>

– Opening ≤ 1 sec.

Cycles until first service (tested at room temp. under

clean and static vacuum

conditions)

Temperature – Valve body ≤ 150 °C (Maximum values: depending – Actuator ≤ 120 °C

on operating conditions and

sealing materials)

Material – Valve body Aluminum (EN AC-42000)

ActuatorAluminum

Plate
Bellows
AISI 316L (1.4404)
AISI 316 Ti (1.4571)

1 million

Seal – Bonnet O-ring FKM (Viton®)

Plate O-ringActuator O-ringFKM (Viton®)FKM (Viton®)

Weight 9 kg / 20 lbs

Mounting position any

Volume of pneumatic actuator 0.3 I / 0.01 ft<sup>3</sup>

Compressed air 4.5 – 7 bar / 65 – 102 psi

min. - max. overpressure

Compressed air connection 1/8" ISO/NPT female

air pressure drop — Valve opened Valve closes leaktight

During actuation
Valve closes leaktight

Created by: LIN	Release date: 08.02.2013	1/2
Modified by:	Release date:	600083EA



## **Product data sheet**

HV angle valve Series 264, DN 100 (ID 4") Ordering No. 26440-QA11-0001

Behavior in case of power failure — Valve closed

Valve closedValve opened

Valve remains closed and leaktight Depending on customer installation

During actuation

Depending on customer installation

Created by: LIN	Release date: 08.02.2013	2/2
Modified by:	Release date:	600083EA