

Product data sheet

HV angle valve Series 264, DN 100 (ID 4") Ordering No. 26440-QE11-0001

Description

ISO-K 100 Flange

Actuator Pneumatic, single acting with closing spring

> without solenoid valve - without position indicator

Feedthrough **Bellows**

Technical data

Pressure range

< 1 · 10⁻⁹ mbar ls⁻¹ - Valve body Leak rate $< 1 \cdot 10^{-9} \text{ mbar Is}^{-1}$ Valve seat

 $1 \cdot 10^{-8}$ mbar to 2 bar (abs)

- In opening direction Differential pressure on the plate ≤ 1.2 bar

- In closing direction ≤ 2 bar

Differential pressure at opening ≤ 1 bar [1 bar with reduced number of cycles]

Conductance (molecular flow) 440 ls⁻¹

Actuation time Closing \leq 1 sec.

Opening ≤ 1 sec.

Cycles until first service (tested at room temp. under

clean and static vacuum

conditions)

Temperature - Valve body ≤ 150 °C (Maximum values: depending - Actuator ≤ 120 °C

on operating conditions and

sealing materials)

Material Valve body AISI 316L (1.4404)

> - Actuator Aluminum

- Plate AISI 316L (1.4404) - Bellows AISI 316 Ti (1.4571)

1 million

Seal - Bonnet O-ring FKM (Viton®)

> - Plate O-ring FKM (Viton®) - Actuator O-ring FKM (Viton®)

Weight 9 kg / 20 lbs

Mounting position any

 $0.3 \, \text{I} / \, 0.01 \, \text{ft}^3$ Volume of pneumatic actuator

Compressed air 4.5 - 7 bar / 65 - 102 psi

min. - max. overpressure

Compressed air connection 1/8" ISO/NPT female

- Valve closed

Behavior in case of compressed Valve remains closed and leaktight air pressure drop - Valve opened Valve closes leaktight

- During actuation Valve closes leaktight

Created by: LIN Modified by:	Release date: 08.02.2013 Release date:	60007E A
		600087EA



Product data sheet

HV angle valve Series 264, DN 100 (ID 4") Ordering No. 26440-QE11-0001

Behavior in case of power failure - Valve closed

Valve closedValve opened

Valve remains closed and leaktight Depending on customer installation

During actuation

Depending on customer installation

Created by: LIN	Release date: 08.02.2013	2/2
Modified by:	Release date:	600087EA