

## **Product data sheet**

## **HV** inline valve Series 265, DN 50 (ID 2") Ordering No. 26534-KE11-0001

**Description** 

ISO-KF 50 Flange

Actuator Pneumatic, single acting with closing spring

> without solenoid valve without position indicator

Feedthrough **Bellows** 

**Technical data** 

 $< 1 \cdot 10^{-9} \, \text{mbar Is}^{-1}$ Leak rate Valve body  $< 1 \cdot 10^{-9} \text{ mbar ls}^{-1}$ 

Valve seat

 $1 \cdot 10^{-8}$  mbar to 5 bar (abs) Pressure range

Differential pressure on the plate In opening direction ≤ 2 bar

- In closing direction ≤ 5 bar

Differential pressure at opening ≤ 1 bar

Conductance (molecular flow) 80 Is<sup>-1</sup>

Closing time ≤ 0.65 sec.

Cycles until first service 3 million

(Tmax 80 °C, under clean

conditions)

Temperature Valve body ≤ 150 °C (Maximum values: depending - Actuator ≤ 120 °C

on operating conditions and

sealing materials)

Material - Valve body AISI 304 (1.4301)

> Actuator Aluminum

- Plate AISI 316L (1.4435 ESU)

- Bellows AISI 316L (1.4404, 1.4435) AISI 316 Ti (1.4571)

FKM (Viton®) - Bonnet O-ring Seal

FKM (Viton®) Plate O-ring FKM (Viton®) Actuator O-ring

Weight 2.0 kg / 4.409 lbs

Mounting position any

0.047 I / 0.0017 ft<sup>3</sup> Volume of pneumatic actuator

4 - 8 bar / 58 - 116 psi Compressed air

min. - max. overpressure

Compressed air connection M5 female (10-32 UNF suitable)

Created by: WARO	Release date: 19.06.2014	1/2
Modified by:	Release date:	755048EA



## **Product data sheet**

HV inline valve Series 265, DN 50 (ID 2") Ordering No. 26534-KE11-0001

Behavior in case of compressed air pressure drop

Valve closedValve opened

During actuation

valve remains closed and leaktight

valve closes leaktight valve closes leaktight

Behavior in case of power failure

Valve closedValve opened

depending on customer installation depending on customer installation

depending on customer installation

Valve openedDuring actuation