



VAT Vakuumventile AG
CH-9469 Haag, Schweiz

Product data sheet

All-Metal Angle Valve, Series 57.0, DN 100 (ID 4")

Ordering No. 57040-GE08-0005

Description

Flange	CF-R DN100
Actuator	manual, hexagon head SW27, with position indicator
Feedthrough	bellows

Technical data

Leak rate	
- To the outside	$\leq 1 \cdot 10^{-10} \text{ mbar ls}^{-1}$
- Seat	$\leq 1 \cdot 10^{-10} \text{ mbar ls}^{-1}$
Molecular flow conductance	380 ls^{-1}
Pressure range	UHV to 5 bar (abs)
Test pressure	1 bar
Differential pressure on the gate	
- in closing and opening direction	$\leq 5 \text{ bar}$
Max. differential pressure at opening	
- in closing and opening direction	1 bar (> 1 bar at reduced cycle lifetime)
Cycles until first service	10'000
Bake-out temperature	
Valve - open	$\leq 450^\circ\text{C}$
- closed	$\leq 350^\circ\text{C}$
Actuator	$\leq 300^\circ\text{C}$
Position indicator	$\leq 80^\circ\text{C}$
Heating and cooling rate	$\leq 60^\circ\text{C h}^{-1}$
Material	
- Body, Mechanism (in contact with media)	1.4435/1.4404, AISI 316 L; 1.4435, AISI 316 L, ESU
- Bellows	1.4404, AISI 316 L
Seal	
- Bonnet, Plate	metal
Mounting position	any
Radiation resistance	
- Valve	$10^8 \text{ Gy (} 10^{10} \text{ rad)}$
- Actuator	$10^8 \text{ Gy (} 10^{10} \text{ rad)}$
- Pos. Indicator	$10^5 \text{ Gy (} 10^7 \text{ rad)}$
Position indicator	
- 1 switch for «open» and 1 switch for «close»	
- Contact rating	$\leq 50 \text{ V AC / DC; } \leq 1.2 \text{ A}$
- 7 pin connector	
Turns per stroke	6.4
Closing torque	90 Nm / 66 lbs
Weight	16.6 kg / 36.5 lbs

Created by: Kurt Sonderegger	Release date: 24.08.2011	Page 1 of 2
Modified by:	Release date:	291145EA



VAT Vakuumventile AG
CH-9469 Haag, Schweiz

Product data sheet

All-Metal Angle Valve, Series 57.0, DN 100 (ID 4")


Ordering No. 57040-GE08-0005

Dimensions

Dim. Drawing

504936

Wiring diagram



Lo = position indicator open

Lg = position indicator closed

Created by: Kurt Sonderegger	Release date: 24.08.2011	Page 2 of 2
Modified by:	Release date:	291145EA