



VAT Vakuumventile AG
CH-9469 Haag, Schweiz

Product data sheet

UHV angle valve, Series 284, DN 16 (ID 5/8")
Ordering No. 28424-KE01-CQS1

Description

Flange		ISO-KF 16
Actuator		Manual actuator
Feedthrough		Bellows
Options	CQS =	- Product: valve type ITER 25 - Gate: seal material EPDM

Technical data¹

Leak rate	- Valve body - Valve seat	$\leq 1 \cdot 10^{-8}$ mbar ls ⁻¹ $< 1 \cdot 10^{-8}$ mbar ls ⁻¹
Leak rate (accidental condition)	- Valve body - Valve seat	$\leq 1 \cdot 10^{-8}$ mbar ls ⁻¹ n/a
Pressure range		$1 \cdot 10^{-8}$ mbar to 1.5 bar (abs)
Differential pressure on the plate	- In either direction	≤ 1.5 bar
Differential pressure at opening		≤ 1 bar
Conductance (molecular flow)		5 ls ⁻¹
Cycles until first service (tested at room temp. under clean and static vacuum conditions)		10'000
Temperature (Maximum values: depending on operating conditions and sealing materials)	- Valve body - Hand wheel	≤ 150 °C ≤ 120 °C
Material	- Valve body - Actuator - Hand wheel ² - Plate - Bellows	AISI 304 (1.4301) Aluminum Plastic AISI 316L (1.4404) AISI 316L (1.4404, 1.4435) AISI 316 Ti (1.4571)
Seal	- Bonnet seal - Plate O-ring	Metal EPDM
Weight		0.34 kg / 0.75 lbs
Mounting position		any
Radiation resistance		10^6 Gy (10^8 rad)
Maximum magnetic field levels		≤ 150 mT
Assembly cleanliness level		ISO Class 8

Related documents

Dimensional drawing No.	951903 Rev -
STEP file No.	951902 Rev -

¹ Values according technical specification D_R8752R v.1.1
² Removable

Created by: BRR	Release date: 14.09.2018	1/1
Modified by: Phil Schneider	Release date: 15.02.2021	953859EA