



VAT Vakuumventile AG
CH-9469 Haag, Schweiz

Product data sheet

All-metal angle valve Series 571, DN 63 (ID 2½")
Ordering No. 57132-RE22-AJH1

Description

Flange		Weld neck N.D. 40 schedule 10S
Actuator		Pneumatic, single acting with opening spring – without solenoid valve – with position indicator 200°C
Feedthrough		Bellows
Options	AJH =	Product: valve type ITER 52; Flange A+B: weld stub flange schedule 10S; Actuator: radiation resistant 10 ⁶ Gy; Position indicator: double; 200°C; Glenair 6 pin connector; 125 °C; radiation resistant 10 ⁶ Gy; Bonnet flange: vacuum feedthrough double bellows; kind of seal double; edge seal; Helicoflex; intermediate pumping; VCR 1/4"

Technical data

Leak rate	– Valve body – Valve seat	< 1 · 10 ⁻⁹ mbar ls ⁻¹ < 1 · 10 ⁻⁹ mbar ls ⁻¹
Pressure range		XUHV to 5 bar (abs)
Differential pressure on the plate	– In opening direction – In closing direction	≤ 5 bar ≤ 5 bar
Differential pressure at opening		≤ 1 bar >1 bar with reduced number of cycles
Conductance (molecular flow)		26 ls ⁻¹
Cycles until first service (Maximum values: depending on operating conditions and valve contamination)	– Normal conditions ¹ – Extreme conditions ²	20 000 1 000
Bake-out temperature (Maximum values: depending on operating conditions and sealing materials)	– Valve body – Actuator – Position indicator	≤ 240 °C ≤ 140 °C (for max. 100h) ≤ 200 °C
Heating and cooling rate		≤ 10 °C h ⁻¹
Material	– Valve body – Gate – Bellows – Actuator	AISI 316L ESR AISI 316L ESR AISI 316L AISI 303; AISI 6150; aluminium
Seal	– Bonnet – Gate – Actuator	metal, silver plated metal, silver plated EPDM
Mounting position		any
Radiation resistance	– Valve body – Actuator – Position indicators	10 ⁸ Gy (10 ¹⁰ rad) 10 ⁶ Gy (10 ⁸ rad) 10 ⁶ Gy (10 ⁸ rad)

¹ Normal conditions: External pressure 0.1 MPa, pressure inside valve 0 MPa, bellows interspace pressure 0.05 MPa temperatures ambient.

² Extreme conditions: External pressure 0.2 MPa, pressure inside valve 0 MPa, bellows interspace pressure 0 MPa, temperature 100 °C

Created by: Kurt Sonderegger	Release date: 23.10.2019	1/2
Modified by: Phil Schneider	Release date: 12.02.2021	1008731EB



VAT Vakuumventile AG
CH-9469 Haag, Schweiz

Product data sheet

All-metal angle valve Series 571, DN 63 (ID 2½")
Ordering No. 57132-RE22-AJH1

Maximum magnetic field levels		≤ 150 mT
Volume of pneumatic actuator		0.45 l / 0.016 ft ³
Compressed air min. – max. overpressure		4.8 – 5.8 bar / 70 – 85 psi
Compressed air connection		G ½" / (USA: ½" NPT)
Actuation time (valid for RT, Ø6mm tubing at 4 bar with flow rate of 400 l/min)	– Closing – Opening	≤ 2.0 sec ≤ 2.0 sec
Weight	– Valve complete – Actuator	9.3 kg / 20.5 lbs 6.9 kg / 15.2 lbs
Behavior in case of compressed air pressure drop	– Valve closed – Valve open	Valve opens Valve stays open
Behavior in case of power failure	– Valve closed – Valve open	Depends on control Depends on control


Related documents

Dimensional drawing No.	995729	Rev A
STEP file No	995728	Rev A

Electrical connections

Position indicator (2x)

Type	Micro switch
Voltage	≤ 50 V AC/DC
Current max.	≤ 1.0 A
Connector on the valve:	8070-2530-02Z16-6PA
Mating connector:*	8070-3039-01Z16-6KA (pins compatible with AWG 20 wire)



Wiring diagram

References

The product data are based on either VAT internally/externally performed lab tests or supplier product information. Relevant references listed on document 838738.

*The mating connector is not part of the valve and needs to be ordered separately at Glenair.

Created by: Kurt Sonderegger	Release date: 23.10.2019	2/2
Modified by: Phil Schneider	Release date: 12.02.2021	1008731EB